

Sisteme si dispozitive de supraveghere si de securitate

I.D.: 44753573

Data publicarii	06.12.19	Coduri CPV	35120000-1
-----------------	----------	------------	------------

Pretul estimativ:	15.889,03 RON - 15.889,03 RON
-------------------	-------------------------------

Descriere: SP6000 cu cutie cu traf + K636 + accesorii buc 1 • NV5-SB - detector digital infrarosu, inalta performanta, cu suport sb100 buc 6 Sirena de exterior autoalimentata cu flash, carcasa dubla policarbonat + metal, autoprotectie contra taierii firelor si a sabotajului, accepta acumulator de 2,3Ah, sigla DSC. buc 1 Acumulator PILOT, 7 AH/12V. buc 2 Buton de panica cu reținere, plastic, NO/NC selectabil. buc 1 Sirena piezo + flash. buc 1 Cablu ecranat 6 x 0,22, PVC alb, antifiacara. ml 150 Accesorii cablaj buc 4 Canal de cablu Pvc 60 mm x 40 mm x 2 m - Strohm ml 30 Canal de cablu Pvc 25 mm x 16 mm x 2 m - Strohm ml 60 Camera bullet de exterior HDCVI, Senzor 1/3" 4 Megapixeli CMOS, rezolutie 25fps@4MP, 25fps@1080P, 25fps@720P, Smart IR 60 m, lentila varifocala 2.7~13.5mm, Day/Night (ICR), AWB, AGC, BLC, DWDR, 2D noise reduction, 0.03Lux/F2.0, 30IRE, 0Lux IR pornit, meniu OSD, temperatura de functionare -40°C~60°C, IP67, alimentare DC 12V, transmisia se face pe cablu coaxial sau UTP (cu videobalun) pe o distanta de maxim 700m/ 4M, 500m/720p, 300m/1080p cu RG59 sau 700m/4M, 700m/720p, 400m/1080p cu RG6, 300m/4M prin cablu UTP buc 1 Camera dome de exterior HDCVI, Senzor 1/3" 4 Megapixeli CMOS, rezolutie 25fps@4MP, 25fps@1080P, 25fps@720P, Smart IR 30 m, lentila 2.7~13.5mm, Day/Night (ICR), AWB, AGC, BLC, DWDR, 2D noise reduction, 0.03Lux@F1.3, 30IRE, 0Lux IR pornit, meniu OSD, temperatura de functionare -40°C~60°C, IP67, IK10, alimentare DC 12V, transmisia se face pe cablu coaxial sau U
