

Switch TP-Link T2600G-52TS, 48-Port Gigabit, Rackmount Kit

I.D.: 44828281

Data publicarii 09.12.19 Coduri CPV 32420000-3

Pretul estimativ: 1.507,00 RON - 1.507,00 RON

Descriere: HARDWARE FEATURES Standards and Protocols IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p Interface 48 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX) 4 1000Mbps SFP Slots 1 RJ45 Console Port 1 Micro-USB Console Port Network Media 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e or above cable (maximum 100m) 1000BASE-X: MMF, SMF Fan Quantity Fanless Physical Security Lock Yes Power Supply 100~240VAC, 50/60Hz Dimensions (W x D x H) 17.3 x 8.7 x 1.73 in. (440 x 220 x 44 mm) Mounting 19" 1U rack mountable Max Power Consumption 33.5W Max Heat Dissipation 114.4 BTU/h PERFORMANCE Bandwidth/Backplane 104Gbps Packet Forwarding Rate 77.4Mpps MAC Address Table 16k Jumbo Frame 9216 Bytes SOFTWARE FEATURES Quality of Service Support 802.1p CoS/DSCP priority Support 8 priority queues Queue scheduling: SP, WRR, SP+WRR Port/Flow- based Rate Limiting Voice VLAN L2 and L2+ Features Static Routing DHCP Relay IGMP Snooping V1/V2/V3 802.3ad LACP (Up to 14 aggregation groups, containing 8 ports per group) Spanning Tree STP/RSTP/MSTP BPDU Filtering/Guard TC/Root Protect Loopback detection 802.3x Flow Control L2PT VLAN Supports up to 4K VLANs simultaneously (out of 4K VLAN IDs) Port/ MAC/Protocol-based/Private VLAN GARP/GVRP Access Control List L2 ~ L4 package filtering based on source and destination MAC address, IP address, TCP/UDP po