

## **Camera supraveghere rotativa Speed Dome PTZ Dahua SD49225DB-HC, 2 MP, 4.8 - 120 mm, IR 100 m, zoom 2**

I.D.: 106330615

Data publicarii 29.11.24 Coduri CPV 32333200-8

Pretul estimativ: 3.216,81 RON - 3.216,81 RON

Descriere: Specificatii Senzor: 1/2.8 inch CMOS Rezolutie: 2 MP (1920 x 1080 pixeli) Lentila varifocala: 4.8 - 120 mm Diafragma: F1.6 - F3.5 Viteza shutter electronic: 1/3 - 1/30000 s Unghi de vizualizare: 60.6° - 3.2° (Orizontal) / 34.1° - 1.8° (Vertical) / 69.4° - 3.7° (Diagonal) Sistem scanare: Progresiv Iluminare minima: 0.005 lux@F1.6 (Color, 30 IRE), 0.0005 lux@F1.6 (B/W, 30 IRE), 0 lux (IR light) RAM: 256 MB ROM: 128 MB Distanta IR: 100 m Control iluminare: Zoom Prio, manual Zoom optic: 25 x Zoom digital: 16 x Control focus: Auto, semi-auto, manual Distanta DORI: Detectie: 1655.2 m Observare: 653.8 m Recunoastere: 331.0 m Identificare: 165.5 m PTZ: Pan: 0° - 360° Tilt: -15° - 90° Viteza PTZ: Pan: 0.1° - 200° / s Tilt: 0.1° - 120° / s Presetari: 300 Tururi: 8 (pana la 32 presetari / tur) Sablon: 5 Scanare: 5 Memorie power-off: Da Protocol PTZ: DH-SD, Pelco-P/D (Auto recognition) Rezolutii inregistrare: 1080p (1920 x 1080), 720p (1280 x 720), D1 (704 x 576 / 704 x 480) Cadre/secunda: 1080p (25/30 fps), 720p (25/30/50/60 fps) Functii: Day / Night, BLC, WDR, HLC, 2DNR, 3DNR, Zoom digital, zoom optic, TVI, CVI, CVBS, AHD BNC: 1 RS-485: 1 Intrare audio: 1 Intrari alarma: 2 lesiri alarma: 1 Alimentare: 12 VDC, 3 A Protectii: IP66, protectie la trasnet TVS 6000V, protectie la supratensiune, protectie la fluctuatii de tensiune Temperatura de functionare: -40°C - 70°C Dimensiuni: Ø160 x 269.9 Greutate: 3.0 Kg Pachetul contine 1 x Camera supraveghere rotativa Speed Dome PTZ Dahua SD49225DB-H