

Firewall - proiect CNFIS-FDI-2023-F-0709

I.D.: 83852803

Data publicarii	20.06.23	Coduri CPV	32420000-3
-----------------	----------	------------	------------

Pretul estimativ:	26.433,39 RON - 26.433,39 RON
-------------------	-------------------------------

Descriere: GE RJ45 WAN Interfaces Minim 2 GE RJ45 Interfaces Minim 14 GE SFP Slots Minim 4 GE RJ45 Management Ports Minim 2 USB Ports Minim 1 RJ45 Console Port Minim 1 Local Storage - Performanță Generală - Enterprise Trafic IPS Throughput 2.2 Gbps NGFW Throughput 1.2 Gbps Threat Protection Throughput 0.9 Gbps Capacitate și performanță Firewall Throughput (1518 / 512 / 64 byte UDP packets) Minim 20 / 18 / 10 Gbps Firewall Latency (64 byte UDP packets) Minim 3 μs Firewall Throughput (Packets Per Second) Minim 13 Mpps Concurrent Sessions (TCP) Minim 2 Million New Sessions/Second (TCP) Minim 130,000 Firewall Policies Minim 10,000 IPsec VPN Throughput (512 byte) 1 Minim 7 Gbps Gateway-to-Gateway IPsec VPN Tunnels Minim 2,000 Client-to-Gateway IPsec VPN Tunnels Minim 10,000 SSL-VPN Throughput Minim 900 Mbps Concurrent SSL-VPN Users (Recommended Maximum, Tunnel Mode) Minim 500 SSL Inspection Throughput 3 Minim 820 Mbps Application Control Throughput (HTTP 64K) 2 Minim 3.5 Gbps CAPWAP Throughput (1444 byte, UDP) Minim 1.5 Gbps Virtual Domains (Default / Maximum) Minim 10 / 10 High Availability Configurations Minim Active-Active, Active-Passive, Clustering Dimensiuni Height x Width x Length (inches) Aproximativ 1.73 x 17.0 x 10 Height x Width x Length (mm) Aproximativ 44 x 432 x 254 Weight Aproximativ 7 lbs (3 kg) Form Factor Rack Mount, 1 RU Power Consumption (Average / Maximum) Aproximativ 35 W / 39 W Power Source Aproximativ 100-240V 60-50Hz Current (Maximum) Aproximativ 100 V / 1 A, 240 V /
