

Afi?or compatibil cu automate din seria GFanuc 90-30 ?i RX3i - 3 buc

I.D.: 6066342

Data publicarii	16.04.15	Coduri CPV	30231300-0
-----------------	----------	------------	------------

Termenul limita pentru depunere:	22.04.15	Pretul estimativ:	10.666,00 RON
----------------------------------	----------	-------------------	---------------

Descriere: Cantitate : 3 buc. Caracteristici tehnice : Caracteristici procesor • Freescale i.MX535 1GHz bazate pe ARM Cortex A8 • 2D/3D Unitate de Procesare Grafica • 32KB Level 1 Instruction/Data Caches • 256KB Level 2 Unified Instruction and Data Cache • Accelerator Media NEON SIMD • Coprocesor vectorial pentru virgula mobila Memorie • minim 512MB DDR2 SDRAM (7") • minim 256MB SLC NAND Flash (7") • minim 512KB Battery Backed SRAM Display • 7", Widescreen TFT LCD • Rezolu?ie minima 800 x 480 (7") • Display capacitiv • Multi-tactil (two-point) Port Ethernet • 1x 10/100BaseT (RJ-45) (7") • Protocol GFanuc TCP/IP Serial I/O • 1x RS-232 COM Port (5-Pin Connector)(7")/ Protocol GE SNP-X • 1x RS-485 COM Ports USB • minim 1x USB 2.0 Storage • 1x SD/SDHC Card Slot Status Indicators • LED de stare în trei culori (portocaliu/verde/ro?u) Sistem Operare • Microsoft® Windows® Embedded Compact 7 Mediu programare * Cimplicity Machine Edition Alimentare • +24VDC ±20% (3-Pin Connector) (7") • Consum maxim: 15W (7") Dimensiuni • Dimensiuni externe: 192(W) x 137(H) x 36(D) mm (7") Mediu • Metoda de racire Convec?ie naturala • Temperatura operare: de la 0 °C pâna la +55 °C • Umiditate: 85% relativa (fara condensare) 30 °C Compatibilitate cu normele • UL 60950; CE (EN 60950-1; EN 61000-6-4,61000-6-2) • FCC Part15 Class A Garantie : 12 luni
