

## SISTEM CONTROL ACCES CU CARTELĂ

I.D.: 40366226

---

Data publicarii	28.11.19	Coduri CPV	42961100-1
-----------------	----------	------------	------------

---

Pretul estimativ: 3.767,52 RON - 3.767,52 RON

---

Descriere: SISTEM CONTROL ACCES CU CARTELĂ FORMAT DIN: - Single-door Access Controller, Accessible Card Reader: 2 Wiegand readers & 2 RS485 readers; Input interface: 4 alarm input, Door Magnetic×1, Door Switch×1, Case Input×2, Tamper-proof×1; Output interface: Door Switch Relay×1, Alarm Relay×1; Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface; Storage with 100,000 cards information and 300,000 access control events = 1 buc - "Cititor de proximitate Kantech, Wiegand 26, distanta de citire 16,5 cm. = 1 buc - Racord flexibil = 1 buc - "Sursa de alimentare ;Tensiune de intrare: 220-240Vca, 50Hz;Tensiune de iesire: 12Vcc, 2A; Temperatura de functionare: -10°C ~ +55°C; Umiditate: 0 ~ 95%, UR; Dimensiuni: 180(L) x 79(l) x 63(H)mm" = 1 buc - Cartela de proximitate dublu format XSF si 26 bit Wiegand, KANTECH = 10 buc - "Bolt electric (fail-safe) cu actiune magnetica; Consum: 900mA/12 Vcc in actionare; 110mA/12 Vcc in standby Forta de retentie: 800kgf; Corp bolt: 205x35x40 mm ; Contraplaca: 90x25x2 mm; Bolt: 16mm diametru, 16 mm lungime = 1 buc - "Buton de iesire incastrabil, iluminat cu LED albastru; Dimensiuni: 114(H) x 70(l) x 40(A)mm lesire contact: NO/NC; Tensiune: 36Vca, 3A = 1 buc - Cablu UTP cat 6 = 10 ml - Canal cablu 16x25 mm = 5 ml - Pozat cablu 6x0,22 mmp = 15 ml - Cablu electric3x1,5 mmp = 15 ml - Acumulator 12V/7Ah = 1 buc - Accesorii = 2 buc - Materiale +Cabluri echipament + Programare +PIF = 1 buc

---