

Multimetru digital cu autoscalare

I.D.: 50818847

Data publicarii 20.10.20 Coduri CPV 38540000-2 31680000-6

Pretul estimativ: 99,16 RON - 99,16 RON

Descriere: Multimetru digital cu autoscalare NCV MS8332C DC Voltage 400mV/4V/40V/400V $\pm(0.5\%+3)$ 600V $\pm(0.8\%+5)$ AC Voltage 4V/40V/400V $\pm(0.8\%+3)$ 600V $\pm(1.0\%+5)$ DC Current 400 μ A/4mA/40mA/400mA $\pm(1.8\%+5)$ AC Current 400 μ A/4mA/40mA/400mA $\pm(2.0\%+8)$ Resistance 400 Ω /4K Ω /40K Ω /400K Ω /4M Ω $\pm(1.0\%+3)$ 40M Ω $\pm(1.2\%+15)$ Capacitance 4nF $\pm(5.0\%+0.6)$ 40nF $\pm(5.0\%+30)$ 400nF $\pm(3.0\%+15)$ 4 μ F/40 μ F/100 μ F $\pm(5.0\%+25)$ Frequency 1~5MHz $\pm(1.5\%+15)$ Duty Cycle 0.5%~99.9% $\pm(2.0\%+5)$ Battery Test 1.5V/9V $\pm(2.0\%+20)$ Automatic measuring range is DMM, full range is 3999 counting. Display: 3 3/4 digits LCD display. Overload protection: full range protection. Data hold function. Relative value measurement. Low voltage display. Over range display ("OL") Automatic power off. Working temperature and humidity: 0°C to 40°C(32°F to 104°F) ; relative humidity <80%RH Storage temperature and humidity: -10°C to 50°C (10°F to 122°F);relative humidity <70%RH Altitude < 2000m Power supply: AAA 2*1.5V Battery Safety class: EN61010-1, CAT III 600V Dimension (LxWxH): 110x58x33mm Weight: about 150g Display: 4000 counts Auto Ranging Auto Power Off Non-Contact Voltage Detection Diode: 1.5V Continuity Buzzer: <50+-20 Ω Data Hold Backlight Low Battery Display.