

---

## Cablu Digitus Cat.6 U/UTP 305 m Gri acu-4611-305

I.D.: 64030900

---

Data publicarii	06.12.21	Coduri CPV	32000000-3
-----------------	----------	------------	------------

---

Pretul estimativ: 349,00 RON - 349,00 RON

---

Descriere: ASSNET250 CAT 6 U-UTP installation cable, 250 MHz Eca (PVC), AWG 23/1, 305 m paper box, sx, grey The ASSNET installation cables assure best performance and link quality for your network 1Gbit Ethernet 250 MHz transmission frequency CPR class Eca The ASSNET250 Cat.6 U/UTP installation cable is characterized by the following cable construction 4x2x AWG23/1 CCA wires and reaches a transmission frequency up to 250 MHz. The PVC jacket is conform to the CPR Euro class Eca. The cable is suitable for building structured cabling in the secondary and tertiary area. Technical Details Physical properties: Conductor: Copper covered aluminum, solid AWG 23/1 Insulation: HD-PE (High Density Polyethylene) Total number of insulated conductors: 8, twisted in 4 pairs Color code: Blue-white, orange-white, green-white, brown-white Individual pair shield: None Overall shielding: None Outer sheath: Eca acc. to EN 50575; PVC Outer sheath diameter (nominal): 0,55 mm nominal Outer sheath color: Grey (RAL 7035) Mechanical properties: Tensile loading: 150N max. Dynamic bending radius: 8x AD mm min. Static bending radius: 4x AD mm min. Shipping- and storage temperature range: -20 °C up to +75 °C Operating temperature range: -20 °C up to +60 °C Installation temperature range: 0 °C up to +50 °C Electrical properties: Impedance: 100±15 Ohm @ 1-100 MHz Capacitance: 40 pF/m nominal @ 800 Hz Capacitance unbalance (pair-ground): 1.5 pF/m max. @ 1 KHz Insulation resistance: 2 GOhm x km min. DC loop resistance:

---