

## Media convertor

I.D.: 40088412

Data publicarii 14.11.18 Coduri CPV 30236000-2 30237300-2

Pretul estimativ: 37.815,00 RON - 37.815,00 RON

Descriere: Media convertor Media Converter (inclusiv gbic pereche). Media converter: Gigabit Ethernet 10/100/1000Base-T to 100/1000Base-X managed converter ● 10/100/1000Base-T to 100/1000Base-X Converter ● Auto-Cross over for MDI/MDIX in TP port ● Auto-Negotiation or Manual mode in TP port ● Supports flow control Enable or Disable ● Supports Jumbo Frame 9K Packet ● Ingress/Egress Bandwidth control ● Supports IEEE802.3ah OAM management ● Firmware upgrade via Web ● Digital Diagnostic (DOM) SFP Support ● Management Password Setting ● Dying gasp (remote power failure detection) ● Supports Link Fault Pass-Through ( LFPT ) Function ● Supports Auto Laser Shutdown (ALS) Function ● Web management on stand-alone. ● Supports D/D function for SFP fiber transceiver ● Supports On-Line F/W upgrade (local) by the Web manager ● Supports 16 Tag VLAN Group ● RMON counters GBIC Single Mode 70KM Module Rețea Tipul de interfață SFP Rata de transfer de date (max) Viteza maximă cu care datele pot fi transmise la un singur dispozitiv la altul. 1000 Mbit/s Conector cu fibră optică LC Rețea standard IEEE 802.3z Tip aparat emisie-recepție SFP ZX Performanță Sprijin Hot-Plug Da Distanță max transfer 70000 m Lungimi de undă 1550 nm Tipul de cablu Fiber optic Condiții de mediu Interval de temperatură de funcționare (T-T) -40 - 75 °C