

SISTEM ION CROMATOGRAF PENTRU ANALIZA DE ANIONI ANORGANICI DIN FAZA LICHIDA

I.D.: 74439343

Data publicarii	19.10.22	Coduri CPV	38432200-4
-----------------	----------	------------	------------

Pretul estimativ: 138.655,00 RON - 138.655,00 RON

Descriere: SISTEM ION CROMATOGRAF PENTRU ANALIZA DE ANIONI ANORGANICI DIN FAZA LICHIDA.
Include: 10 228-65008-58 LC-20ADSP Solvent Delivery Pump Parallel-type double plunger solvent delivery unit (40 MPa), seals and suction filter optimized for use in ion-chromatography. - 1,00 PC 20 228-45567-91 AUTOMATIC RINSING KIT - 1,00 PC 30 228-65508-58 Reservoir Tray, Reservoir tray, holds up to eight 1 L bottles. - 1,00 PC 35 961-10010-06 Kit 1.5; sc9; gl c; PP-Cap; sil/PTFE - Kit with vial and cap + septa, consisting of 1.5 ml short thread vial, 9 mm screw neck, wide opening, clear 1st hydrol. Class glass, label and filling lines, flat bottom, 32 x 11.6 mm; red short thread PP-cap, 9 mm screw thread, with 6 mm center hole; septa white / red silicone / PTFE, 55° shore A, 1 mm thickness, UltraClean; 100 pcs. per pack - 2,00 PC 40 228-65018-58 DGU-403 Degassing unit (3 channel) Three-channel degassing unit - 1,00 PC 50 228-65501-58 CBM-40lite system controller Substrate-only system controller to be embedded in solvent delivery unit. Can control up to 4 additional modules. - 1,00 PC 60 228-65105-58 SIL-20A Autosampler HPLC autoinjector with direct injection mechanism. The pressure limit is 20 MPa. - 1,00 PC 70 228-65201-58 CTO-40S Column Oven Slim column oven, forced air circulation type. Temperature range from room temperature -10°C to 85°C. - 1,00 PC 80 228-65310-58 CDD-10Avp Conductivity Detector Conductivity Detector - 1,00 PC 90 980-05272 Sistem PC configuratie gata de lucru - 1,00 PC
