

Camera supraveghere exterior IP Hikvision AcuSense DS-2CD2663G2-IZS, 6 MP, IR 60 m, 2.8 - 12 mm, mot

I.D.: 99542397

Data publicarii 02.07.24 Coduri CPV 32333200-8

Pretul estimativ: 2.272,24 RON - 2.272,24 RON

Descriere: Specificatii Senzor: 1/2.8 inch progressive Scan CMOS Sensibilitate: 0.005 LUX (color) / 0 LUX (cu IR, alb-negru) Viteza shutter electronic: 1/3s la 1/100.000s Functii speciale: WDR (120db), ROI (1 zona fixa), BLC, HLC, 3D DNR Lentila varifocala: 2.8 - 12 mm (motorizat) Unghi de vizualizare: 106° la 32° (orizontala) x 56° la 18° (verticala) x 127° la 37° (diagonala) Diafragma: F1.6 Distanta iluminator IR: 60 m Rezolutie video: 6 Megapixeli (3200 x 1800 pixeli) Cadre/secunda: 20/30 FPS Bit Rate: 32kbps la 16Mbps Compresie video: H.264/H.265 Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP API: ONVIS (profil S, profil G), ISAPI, SDK Software compatibil: iVMS-4200, Hik-Connect, Hik-Central Retea: 1x RJ45 10M/100M Capacitate de stocare: card microSD de pana la 256 GB (nu este inclus) Intrare/iesire audio: 1/1 Intrare/iesire alarma: 1/1 Evenimente basic: detectia miscarii Detectie faciala Protectie perimetrala: detectie trecere linie virtuala, detectie intruziune, suporta clasificare om/vehicul Metoda legatura: incarcare in FTP/card memorie/NAS, notificare centru supraveghere, inregistrare la declansare, captare imagine la declansare, trimitere email alimentare: 12VDC, 1.08A, PoE (802.3at, 42.5 V to 57 V), 0.36 A to 0.27 A Consum: 13W (12VDC), 15W (PoE) Grad de protectie: IP67, IK10 Carcasa: Aluminiu Dimensiuni: 308.5 x 97.9 x 93 mm Greutate: 1385g Temperatura de functionare: -3