

Piese si componente IT&C

I.D.: 31769663

Data publicarii	02.11.18	Coduri CPV	30237200-1
-----------------	----------	------------	------------

Termenul limita pentru depunere:	10.11.18	Pretul estimativ:	10.050,00 RON
----------------------------------	----------	-------------------	---------------

Descriere: 1. Sursa ATX 500 W, Ventilator 1 x 120 mm, minim 2 x molex si 2 x SATA Buc. 10; 2. Memorie laptop DDR 2 - capacitate 2Gb Buc. 2; 3. Acumulator UPS 12V/7 AH Buc. 18; 4. Acumulator UPS 12V/5.8 AH (LxWxH - 90x70x101 mm/ 90 x 70x 107 mm la borne) tip conectori F2/T2 (6.3 mm) Buc. 16; 5. Ansamblu casca microfon MTH 800 cod FTN6583A Buc. 30; 6. Cordon spiralat pentru receptor telefon minim 4,5m, alb, RJ 9 Buc. 100; 7. Mouse interfata USB, rezolutie 1000 DPI, sensor optic, butoane/rotite 3/1 Buc. 20; 8. Sursa alimentare in comutatie 12 Vc.c. minim 20 A, pentru statii radio Buc. 5; 9. Unitate de stocare inregistrare video DVR : Compresie video H.264, Intrari video analog si HDTV : 8-ch, BNC interface (1.0Vp-p, 75 ohm), compresie audio G7.11, Intrare audio : 1-CH, interfata intrari audio, iesire VGA : 1920x108/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz, Iesire HDMI : 1920x108/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz, Rezolutie : MAIN stream : 1080P(non-real-time) / 720P/ WD1/VGA/4CIF/CIF;Sub-stream : WD1 (non-real-time) / 4 CIF (non-real-time) / CIF/QCIF/QVGA, Steam Type : video/video&audio, Rezolutie inregistrari : 1080P/720P/VGA/WD1/4CIF/CIF/QVGA/QCIF. tip inregistrare : manuala/dupa orar/la detectie/la alarma, Interfata HDD - 1 x SATA, Interfata de retea 1 x RJ45, Interfata USB, alimentare 12 V cu alimentator inclus, garantie 24 luni Buc. 2; 10. Camere video fixa , tip BULLET, senzor imagine 2 megapixeli CMOS, rezolutie 1080P@25Fps, tehnologie AHD/HDCVI/HDTV, sensibilitate 0,01 Lux color,0Lux Alb/Negru (IR), lentila varifocala 2,8-12mm, protectie IP66, Infrarosu 40 m, filtru IR CUT AUTOMAT, alimentare 12 V, Kit prindere de perete inclus, suport ajustabil PAN 0-360 grade, tilt : 0-90 grade, rotatie 0-360 grade, garantie 2 ani Buc. 8; 11. Surse alimentare camera CCTV, 12Vcc, minim 4A, carcasa de plastic inchisa, cablu alimentare 220V si cablu cu mufa pentru alimentatare camere video Buc. 5; 12. Switch 8 porturi RJ 45 minim 100 MB/s Buc. 10; 13. HDD surveillance 2Tb, Sata, 64Mb cache, garantie 24 luni Buc. 2;