

Achizitie de echipamente pentru comunicatii si informatica

I.D.: 40034839

Data publicarii: 29.10.18
Coduri CPV: 32581100-0 30233140-4 30125100-2 32562000-0

Pretul estimativ: 28.347,50 RON - 28.347,50 RON

Descriere: Sheath Printing Q5+ F/UTP MESS. 4P 24AWG TIA/EIA 568B2 ROHS CE 001m-500m Category F/UTP/CAT5e-4P-PVC UV Protected Test Standard ISO/IEC11801、 TIA/EIA 568B YD/T1019-2001 Cable IEC 61156 EN 50288-3-2 System EIA/TIA 568-B.2-CAT5e ISO 1181 Edition 2-CLASS D EN 50173 Edition 2-CLASS D 1. KITUL CONTINE UN SSD SI UN ADAPTOR LA PORTURI 3.5 CU CABLU SATA SI ACCESORIILE AFERENTE CARACTERISTICI GENERALE Form Factor: 2.5 inch Capacitate: 512 GB Interfata SATA 3 Rata de transfer la citire (MB/s) :550 MB/s Rata de transfer la scriere (MB/s): 520 MB/s Altele: Bulk Dimensiuni (W x D x H mm): 100.076 x 69.85 x 6.858 mm Greutate (g): 90 g Tip Memorie: SSD CABLU FIBRA OPTICA MULTITUB LTC 2KN TKF 24 FIBRE 2000N METALFREE Cablu Fibra Optica MULTI TUBE (Loose tube gel filled), metalfree, protectie ultraviolete, protectie rozatoare. 24 fibre (2x12). Diametru: 10mm, Greutate: 76kg/km; Tensiune intindere: 2000N; Raza min.: 230mm; Dimensiuni role: 2-4km Fibre optic cable Single mode Type-LTC Description 24x SM G.657.A1 (12x2) Net weight-76 kg/km Properties Test procedures-EC 60794-1-2 Application-Outside Cable metal free-Yes Installable by blowing-Yes Strain relief-Yes UV Resistant-Yes Halogen free (acc. EN 50267-2-2)-Yes Longitudinal water blocking-Yes Number of fibres-24 Number of fibres per tube-12 Number of cores-2 Type of tube-Loose tube, gel filled Fibre type-Single Mode Number of Layers-1 Colour of outer sheath-Black Outer sheath material*PE Characteristics of use Properties Longitudinal watert