

SISTEM CONTROL ACCES CU CARTELĂ

I.D.: 72516988

Data publicarii	22.08.22	Coduri CPV	42961100-1
-----------------	----------	------------	------------

Pretul estimativ: 5.746,75 RON - 5.746,75 RON

Descriere: SISTEM CONTROL ACCES CU CARTELĂ FORMAT DIN: - Single-door Access Controller, Accessible Card Reader: 2 Wiegand readers & 2 RS485 readers; Input interface: 4 alarm input, Door Magnetic×1, Door Switch×1, Case Input×2, Tamper-proof×1; Output interface: Door Switch Relay×1, Alarm Relay×1; Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface; Storage with 100,000 cards information and 300,000 access control events DS-K2601 = 1 buc - Cititor de proximitate Wiegand 26, distanta de citire 16,5 cm DS-K1107E = 2 buc - Cartela de proximitate dublu format XSF si 26 bit Wiegand, KANTECH P 10 SHL = 65 buc - Racord flexibil DLK 401 S = 1 buc - Sursa de alimentare ,Tensiune de intrare: 220-240Vca, 50Hz, Tensiune de iesire: 12Vcc, 2A, Temperatura de functionare: -10°C ~ +55°C, Umiditate: 0 ~ 95%, UR, Dimensiuni: 180(L) x 79(l) x 63(H)mm - 1 buc - Electromagnet forta 180 Kg, 12/24V, contact magnetic YM-180N -1 buc - Suport electromagnet forta 500 Kg, 12/24V, MBK-180I - 1 buc - Amortizor hidraulic, greutatea usii actionate 40-65 Kg SA 6033W - 1 buc - Buton de iesire incastrabil, iluminat cu LED albastru, Dimensiuni: 114(H) x 70(l) x 40(A)mm, lesire contact: NO/NC, Tensiune: 36Vca, 3A , Accesorii: PBK-814D (LED) -1 buc - Cablu UTP cat 6 = 15 ml - Canal cablu 16x25 mm = 10 ml - Pozat cablu 6x0,22 mmp = 15 ml - Cablu electric 3x1,5 mmp = 15 ml - Acumulator 12V/7Ah = 2 buc - Materiale +Manopera pozare cabluri echipament + Programare +PIF = 1 buc
