

## **NVR Dahua NVR5216-16P-4KS2E cu 2 HDD 4Tb**

I.D.: 52696447

---

Data publicarii	15.12.20	Coduri CPV	32235000-9
-----------------	----------	------------	------------

---

Pretul estimativ: 2.092,00 RON - 2.092,00 RON

---

Descriere: POE (Power Over Ethernet - Alimentare prin cablul de retea) Interfata: 16x porturi (IEEE802.3at/ af) Porturile 1 - 8: ePoE & EoC Inregistrare Rezolutie inregistrare: 12Mp, 8Mp, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 1.3Mp, 720P, D1 Mod inregistrare: Manual, Orar (Normal, Detectie de miscare, Alarma, IVS), Stop Intervalul de inregistrare: 1 - 120 min (default: 60 min), pre-inregistrare 1 - 30 sec, post-inregistrare 10 - 300 sec Audio/Video Intrari video IP: 16x canale lesiri video: 1x HDMI, 1x VGA Rezolutie redare: HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1280x720, 1024x768 Comunicare bidirectionala: 1 canal intrare, 1 canal iesire, RCA Compresie video: Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Functii speciale: Functii IVS (Tripwire, detectie intrusi, detectie obiect lipsa/ abandonat, detectie faciala) heat map, people counting, recompunere imagine), tehnologie ANR (Automatic Network Replenishment) Vizualizare de pe telefon: iPhone, iPad, Android Stocare HDD: 2x porturi SATA III, pana la 10 TB/HDD 2 HDD 4TB incluse Backup: USB, retea Interfete auxiliare USB: 2x USB (USB 3.0, USB 2.0) RS485: 1x Port, pentru Control PTZ RS232 1x Port, tastatura si comunicatie PC Intrari/lesiri Alarma: 4/2 Caracteristici generale Temperatura de functionare: de la -10°C pana la +55°C Ventilator: Smart fan, ajustare automata a vitezei Alimentare: Single, AC100V ~ 240V, 50 ~ 60 Hz Consum: NVR: <15.2W (fara HDD) PoE: maxim 25.5W/ port, 130W total

---