
Kit Microfon Shotgun Rode NTG4 + Antivant Rode WS6

I.D.: 52707046

| | | | |
|-----------------|----------|------------|------------|
| Data publicarii | 17.12.20 | Coduri CPV | 32351000-8 |
|-----------------|----------|------------|------------|

Pretul estimativ: 2.015,12 RON - 2.015,12 RON

Descriere: Conditii refuzate: Specificatii tehnice: Principiu acustic gradient liniar Model directional Super-cardioid Gama frecvente 20 - 20,000 Hz; optiune HPF (high-pass filter) la 75 Hz Sensibilitate -32 dB re 1V/Pa (25 mV la 94 dB SPL) +/- 2 dB la 1,000 Hz. Impedanta iesire 200 ohm Zgomot echivalent 16 dBA SPL (per IEC651) lesire maxima 7 dBu (la 1 kHz, 1% THD in 1 kOhm) Interval dinamic 119 dB (per IEC651) SPL maxim 135 dB Signal to Noise Ratio 78 dB SPL (per IEC651) Baterie fara Conector iesire 3-pin XLR, balanced output between Pin 2 (+), Pin 3 (-) and Pin 1 (ground) Dimensiuni 22.00 x 225.00 mm Greutate 126.00 g
