

Echipamente de sonorizare - TEREN

I.D.: 68006022

Data publicarii	04.04.22	Coduri CPV	32342410-9
-----------------	----------	------------	------------

Pretul estimativ: 16.800,00 RON - 16.800,00 RON

Descriere: Echipamente de sonorizare mobila de teren compus din; - Boxe active 4 bucati - Microfoane fara fir 2 bucati - Mixer audio 6 ch Model BIEMA B2-115 POWER Boxa Activa Mobila Frequency response 60Hz-18KHz Driver BML-T1506; BMH-A5S Directivity angle H80°xV40° Impedance 4 ohm AES power 450W Peak powr 1800W Sensitivity 98dB Maximum SPL 131dB Connector Servo-balanced XLR connector Servo-balanced Input impdeance 20K ohm Sensitivity(line) - 4dB to +18 dB Limiter Opto-controlled Mains voltage 180-260V 50Hz Fuse 180-260V T10A Mains connector Standard IEC connector Product/shipping dimensions(WxDxH) 450x408x685(500x450x730)mm N.W/G.W 28.0kg/31.5kg Model Biema UHF Set Microfon fara fir Frequency range UHF 640-690MHz Modulation mode PLL Bandwidth 50MHz Channel 200 Channel interval 25 KHz Stability ±0.0005% Dynamic range 100dB Max deviation ±80 KHz Frequency response 20Hz-20 KHz ±3dB S/N >85dB Distortion <0.5% Operation temperature -10°C~ 60°C T.H.D <0.5% (at 10KHz Deviation) Power supply DC 12V~500MA Audio output Balanced & unbalanced LCD display Frequency, RF input level, AF level, Muting RF level and wireless channel no. Receiver specifications True-Diversity receiving Mode PLL synthesized oscillation mode Inter frequency First 110MHZ, second; 10.7MHz Antenna type BNC type/50 Ohms Sensitivity 12 dBµV (80dBS/N) Sensitivity range 12-32 dBµV Spurious emission ≥75dB Max audio output +10 dBV Transmitter specifications RF output: Hi 30mW: LO: 10 mW (meet CE/FCC regular) Operation battery AA x 2 L
