

UPS Riello 3000VA/2700W

I.D.: 64378993

Data publicarii	15.12.21	Coduri CPV	31154000-0 31430000-9
-----------------	----------	------------	-----------------------

Pretul estimativ: 3.645,00 RON - 3.645,00 RON

Descriere: UPS Riello 3000VA/2700W - nu este echipat cu baterii INPUT Rated power 3000 VA Voltage 220 / 230 / 240 V Voltage tolerance 230 V $\pm 20\%$ Frequency 50 / 60 Hz ± 5 Frequency tolerance 50 Hz $\pm 5\%$ / 60 Hz $\pm 5\%$ Power factor > 0.98 Current distortion $\leq 7\%$ BY PASS Voltage tolerance 200 / 253 V Frequency tolerance Frequency selected (from ± 0.5 Hz to ± 5 Hz configurable) OUTPUT and INVERTER OUTPUT Rated power 3000 VA Active power 2700 W Crest factor (I_{peak}/I_{rms}) 3 : 1 Waveform Sinusoidal Frequency Selectable: 50 Hz or 60 Hz or self-learning Voltage distortion with non-linear load $\leq 3.5\%$ Voltage distortion with linear load $< 2\%$ OVERLOAD TIMES Load = 150% 0.5 sec Load = 125% 4 sec. BATTERIES Type VRLA AGM maintenance-free lead based Typical recharge time 2-4 h ENVIRONMENTAL Color Black Communication USB / DB9 with RS232 and contacts / Slot for communications interface Accessories provided Power cable, serial cable, USB cable, safety manual, quick start guide Surge capability 300 J Line-Interactive/Smart Active efficiency 98% Noise < 40 [bBA] (ECO Mode) Operating temperature 0 °C - +40 °C Relative humidity 5-95% non-condensing Standards European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant -- Classification in accordance with IEC 62040-3 VFI - SS - 111 DATA Weight 31 kg Dimensions (h w d) (T- 450x87x625) (R- 2Ux19"x625) mm
