

## Camera supraveghere IP Speed Dome Hikvision AcuSense DS-2DE7A432IW-AEB(T5), 4 MP, IR 200 m, 5.9 - 18

I.D.: 70512035

Data publicarii 23.06.22 Coduri CPV 35125300-2

Pretul estimativ: 2.100,00 RON - 2.100,00 RON

Descriere: Specificatii Specificatii Camera Senzor: 1/2.8 inch Progressive Scan CMOS Rezolutie: 4 Megapixeli (2560 × 1440p) Viteza shutter electronic: 1/1 s - 1/30000 s Sensibilitate: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@(F1.5, AGC ON), 0 Lux cu IR pornit Distanta iluminator IR: 200 m Alarma vizuala: da, lumina alba stroboscopica Day & Night IR cut Zoom Digital: 16X Zoom Optic: 32X Lentile Lentila varifocala: 5.9 - 188.8 mm (motorizata) Diafragma: F1.5 Unghi de vizualizare: 50.8° - 2.6° / 29.4° - 1.5° / 57.4° - 3° (orizontala, verticala, diagonala) PTZ Unghi de miscare Pan: 360° Unghi de miscare Tilt: -15° - 90° (auto flip) Viteza Pan: configurabila de la 0.1° la 160°/s, presetare viteza 240°/s Viteza Tilt: configurabila de la 0.1° la 120°/s, presetare viteza 200°/s Numar presetari: 300 Scanare patrula: 8 patrule, pana la 32 presetari pentru fiecare patrula Functie oprire memorie: Da Sarcini programate: presetat, scanare model, scanare patrulare, scanare automata, scanare inclinata, scanare aleatoare, scanare cadru, scanare panorama, repornire dome, reglare dome, iesire auxiliara Video Cadre/secunda: Main Stream: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720); / 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720); Sub Stream: 50Hz: 25fps (704 × 576, 640 × 480, 352 × 288); / 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240); Third Stream: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288); / 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480)