

## Incarcator autospeciala Iveco-Magirus

I.D.: 57369861

---

Data publicarii	26.05.21	Coduri CPV	31158100-9
-----------------	----------	------------	------------

---

Pretul estimativ: 6.500,00 RON - 6.500,00 RON

---

Descriere: Incarcatoe autoaspeciala Iveco-Magirus: Tip VAC 2416 F 3A II. Specificatie tehnica este urmatoarea: Charging power in [V]/[A] 24 / 16 Rated voltage (AC) in [V] 230 Operating voltage range (AC): 190 V - 265 V (full charging power), briefly (5 s) 300 V Sinusoidal power factor correction (CosPhi =1): yes Power consumption (AC): 520 W current consumption Current consumption (230 V AC): 2.7 A Sinusoidal power factor correction (CosPhi = 1) yes Battery capacity in [Ah] 30 - 160Ah Charging current in [A] 16 Secondary charge output "S" in [A] 2 Reverse current from battery (mains failure): <0.6 mA Charging characteristic IU1oU2 Battery type adjustable Acid, gel, AGM Number of charge outputs 2 + S Automatic battery regeneration 2x a week yes Protection against reverse polarity, short circuit, reverse discharge yes Parallel/buffer operation for co-supply of consumers yes Compensation of voltage losses on the charging lines yes Inputs for sensor lines yes Charging current distributor yes Power supply function yes Temperature-controlled, speed-controlled fan yes Connection for remote display, remote control and remote operating display yes Number of temperature sensors 1 Unit installation position any Temperature range [°C] -20 to +45 Degree/class of protection IP 21 / 2 Dimensions incl. mounting flanges, without connections (WxHxD) [mm] 210 x 160 x 72 Weight in [g] 1450 Ambient conditions, humidity max. 95 % RF, non-condensing Safety regulations EN 60335-2-29 Mark of conformity CE Scope

---