

## **Acumulator 12V 9Ah VRLA Ultracell UL9-12, ACUMULATORI 12V 9A, ACUMULATOR VRLA 12V 9A**

I.D.: 41947099

Data publicarii 11.02.19 Coduri CPV 31430000-9

Pretul estimativ: 731,10 RON - 731,10 RON

Descriere: Acumulator 12V 9Ah VRLA Ultracell UL9-12 Ultracell acumulator VRLA 12V, 9Ah PN: C7485010  
PN: UL9-12 Garanție acordată de producător, 12 luni Specificația fizică Lungime  $151 \pm 2$  mm  
Lățime  $65 \pm 2$  mm Înălțimea containerului  $93,5 \pm 2$  mm Înălțime totală (cu terminal)  $99 \pm 2$   
mm Greutate aproximativă 2,45 kg Fisa tehnica - <http://ultracell.net/datasheets/UL9-12.pdf>  
Specifications Nominal Voltage 12V Nominal Capacity (20HR) 9AH Terminal Type Standard  
Terminal F2 Optional Terminal F1 Container Material Standard Option ABS Flame Retardant  
Option (FR) ABS (UL94:VO) Rated Capacity 20hr, 1.80V/cell, 25°C 9.00 AH/0.425A 10hr,  
1.80V/cell, 25°C 8.37 AH/0.791A 5hr, 1.75V/cell, 25°C 7.22 AH/1.45A 1hr, 1.60V/cell, 25°C  
5.34 AH/5.34A Max Discharge Current 127.5A (5s) Internal Resistance Approx 18m  
Discharge Characteristics Operating Temp. Range Discharge: -15 ~ 50°C Charge: 0 ~ 40°C  
Storage: -15 ~ 40°C Nominal Operating Temp. Range  $25 \pm 3$ °C Cycle Use Initial Charging  
Current less than 2.55A.Voltage 14.4V ~ 15.0V Temp. Coefficient -30mV/°C Standby Use No  
limit on Initial Charging Current Voltage 13.5V ~ 13.8V Temp. Coefficient -20mV/°C Capacity  
affect by Temperature 40°C 103% 25°C 100% 0°C 86% ref. 152/28.01.2019 IT