

Sistem de supraveghere video cu 2 camere video high definition

I.D.: 57209829

Data publicarii	19.05.21	Coduri CPV	32323500-8
-----------------	----------	------------	------------

Pretul estimativ: 3.823,53 RON - 3.823,53 RON

Descriere: DVR STAND ALONE HIGH DEFINITION 4MP - DVR 4 ch. video, AUDIO HDTV, Inregistrare: 4 MP lite/1080P @15fps, 1080pLite/720P/WD1/D1 @ 25fps, Stream: 3MP-CH1 / 4MP lite /1080P/720P/WD1/D1, Compresie: H265 Pro+/H265/H264/H264+ Camere suportate: HDTV, AHD,CVI Analog + 2 ch. IP max 6MP; Redare: 1-4 canale sincronizate; Audio IN: 4 x audio HDTV over coaxial, 1 x analogic RCA; Intrari: 4 x BNC; LAN 10/100, 2xUSB,, Iesiri: HDMI 1080P, VGA - (simultan); 1 audio, Stocare: 1 x HDD SATA max 6TB. Alimentare: 12V DC, Consum: 8W (fara HDD) - 1 buc Camera video SENSIBILITATE FOARTE BUNA LA LUMINA SCAZUTA - 2.0MP, lentila 2.7-13.5 mm, IR 70M, Senzor: 2MP CMOS Image Sensor; Rezolutie: 1920(H)x1080(V), 1080P@25fps,, Lentila: motorizata 2.7-13.5mm, unghi vizualizare 102° - 31°, AUTOFOCUS; Iluminare min: 0.005 Lux (F1.2,AGC ON), 0 Lux IR pornit, , Distanta IR: EXIR2.0 pana la 70 metri, IR Cut Filter; Raport S/N: >62dB; Semnal video: TVI/AHD/CVI/CVBS selectabil din dipswitch,, Temp. de functionare: -40°C~60°C,, Alimentare: 12 VDC±15%, consum max. 7.7W; Carcasa: metalica culoare alba - tip "bullet", IP67; - 2 buc Sursa in comutatie 13.8V/50W/4A , Curent maxim: 4 A,, Protectie la suprasarcina/scurtcircuit, Temp. de operare: -30 ~ +70°C, Carcasa metalica de protectie, Putere nominala la iesire: 50,4 W, Tensiune intrare : 85 - 264 V/AC ± 10% 50/60 Hz - 2 buc Doza derivatie pentru mascarea si protejarea conexiunilor efectuate la camera de supraveghere. Material plastic - 2 buc Hard disk special conceput
