

Sisteme de supraveghere (Rev.2)

I.D.: 80931379

Data publicarii	10.04.23	Coduri CPV	35125000-6
-----------------	----------	------------	------------

Pretul estimativ: 346,63 RON - 346,63 RON

Descriere: Specificatii Senzor 4MP CMOS Progresiv 1/3 inch Rezolutie 4 Megapixeli (2560 x 1440 pixeli) Cadre pe secunda 20 - 30 FPS Sensibilitate Color: 0.01 lux (F2.0, AGC ON) B/W: 0 lux cu IR Viteza shutter electronic 1/3 sec la 1/100.000 sec Lentila fixa 4 mm Deschidere F2.0 Distanta Iluminator IR Pana la 20 m Ajustare unghi Pan: 0° - 360°, Tilt: 0° - 180°, Rotire: 0° - 360° Unghi de vizualizare Orizontala 83.2°, Verticala 45.5°, Diagonala 98.3° Compresie video Stream principal: H.265+/H.264+/H.265/H.264 Sub Stream: H.265/H.264/MJPEG Bit Rate video 32 Kbps - 8 Mbps Compresie audio G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC Bit Rate audio 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 - 160 Kbps (MP2L2)/16 - 64 Kbps (AAC) Frecventa de esantionare audio 8 kHz/16 kHz Filtrarea zgomotului din mediul inconjurator Da Protocoale TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS Vizualizare simultana Pana la 6 canale API Interfata de retea video deschisa, ISAPI Utilizator/Gazda Pana la 32 de utilizatori. 3 niveluri: administrator, operator si utilizator Client iVMS-4200, Hik-Connect Comutator Zi/Noapte Zi, Noapte, Auto, Program Functii speciale ROI (1 regiune), BLC, 3D DNR, WDR 120 dB, microfon, anti-flicker, heartbeat, oglinda, protectie cu parola, masca confidentialitate, watermark, filtru adresa IP, detectie miscare, alarma intemperii video, exceptie, Saturatie, luminozitate, c
