

## **MikroTik AC Access Point RBcAPGi-5acD2nD, cAP ac, 2.4/5GHz, 2x Gigabit, wall/ceiling**

I.D.: 74161495

---

Data publicarii	11.10.22	Coduri CPV	32420000-3
-----------------	----------	------------	------------

---

Pretul estimativ: 734,00 RON - 734,00 RON

---

Descriere: Specifications Product code RBcAPGi-5acD2nD Architecture ARM 32bit CPU IPQ-4018 CPU core count 4 CPU nominal frequency 716 MHz Dimensions Round case: ø 136 mm, height: 30 mm; Square case: 145 mm x 145 mm x 30 mm RouterOS license 4 Operating System RouterOS Size of RAM 128 MB Storage size 16 MB Storage type FLASH MTBF Approximately 100'000 hours at 25C Tested ambient temperature -40°C to 50°C IPsec hardware acceleration Yes ===== Wireless capabilities Details Wireless 2.4 GHz Max data rate 300 Mbit/s Wireless 2.4 GHz number of chains 2 Wireless 2.4 GHz standards 802.11b/g/n Antenna gain dBi for 2.4 GHz 2 Wireless 2.4 GHz chip model IPQ-4018 Wireless 2.4 GHz generation Wi-Fi 4 Wireless 5 GHz Max data rate 867 Mbit/s Wireless 5 GHz number of chains 2 Wireless 5 GHz standards 802.11a/n/ac Antenna gain dBi for 5 GHz 2.5 Wireless 5 GHz chip model IPQ-4018 Wireless 5 GHz generation Wi-Fi 5 WiFi speed AC1200 ===== Ethernet Details 10/100/1000 Ethernet ports 2 ===== Powering Details Number of DC inputs 1 (PoE-IN) Max power consumption 24 W Max power consumption without attachments 13 W Cooling type Passive PoE in 802.3af/at PoE in input Voltage 17-57 V ===== PoE-out Details PoE-out ports Ether2 PoE out Passive PoE up to 57V Max out per port output (input 18-30 V) 500 mA Max out per port output (input 30-57 V) 400 mA Max total out (A) 500 mA

---