

## Placa de baza ASUS PRIME H410M-D Intel LGA1200 mATX

I.D.: 64592924

---

Data publicarii	21.12.21	Coduri CPV	30237140-2
-----------------	----------	------------	------------

---

Pretul estimativ: 2.417,59 RON - 2.417,59 RON

---

Descriere: Placa de baza Asus PRIME H410M-D Socket LGA 1200 CPU Intel® Socket 1200 for 10th Gen Intel® Core™, Pentium® Gold and Celeron® Processors \* Supports Intel® 14 nm CPU Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0\*\* \* Refer to [www.asus.com](http://www.asus.com) for CPU support list \*\*Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types. Chipset Intel® H410 Memory 2 x DIMM, Max. 64GB, DDR4 2933/2800/2666/2400/2133 MHz Non-ECC, Un- buffered Memory \* Dual Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) OptiMem \* 10th Gen Intel® Core™ i9/i7 CPUs support 2933/2800/2666/2400/2133 natively, Refer to [www.asus.com](http://www.asus.com) for the Memory QVL (Qualified Vendors Lists). Graphic Integrated Graphics Processor \* 1 x D-Sub 1 x HDMI 1.4b \*Graphics specifications may vary between CPU types. Expansion Slots Intel® 10th Gen Processors 1 x PCIe 3.0 x16 (x16 mode) Intel® H410 Chipset 2 x PCIe 3.0 x1 Storage Total supports 1 x M.2 slots and 4 x SATA 6Gb/s ports Intel® H410 Chipset : 1 x M.2 Socket 3, with M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 X2 mode)\*1 4 x SATA 6Gb/s port(s) LAN Realtek® RTL8111H Audio Realtek ALC887 7.1-Channel High Definition Audio CODEC \*2 - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio PCB layers - Premium Japanese audio capacitors mATX Form Factor 8.9 inch x 7.9 inch (

---