

PACHET CONFORM ANUNT ADV1242037

I.D.: 62028050

Data publicarii	15.10.21	Coduri CPV	35125300-2
-----------------	----------	------------	------------

Pretul estimativ: 5.123,00 RON - 5.123,00 RON

Descriere: x DS-7616NI-K2/16P NVR 16 canale, incoming 160 Mbps, H265, rezolutie de inregistrare pana la 8MP, VGA, HDMI, CVBS, 2xUSB, 2 interfete SATA (accepta HDD de 6TB), audio 1xIN, 1xOUT, alarma 4xIN, 1xOUT, 16x porturi PoE, 220VAC, 20W, compatibil Android si los 6 x DS-2CD2T43G2-2I 2.8mm Camera IP bullet, 4MP, IR 60m, lentila fixa 2.8mm, detectie faciala si alte functii inteligente, WDR 120dB, 3D DNR, BLC, HLC, ROI, slot card micro SD/SDHC/SDXC 256GB, streaming triplu, EXIR, IP67, 12VDC/PoE 2 x DS-2CD1123G0E-I Descriere Camera de supraveghere Hikvision IP Dome, DS-2CD1123G0E-I(2.8mm); 2MP; 1/2.8" progressive scan CMOS; Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON); 3D DNR, DWDR; Fixed lens: 2.8mm; Video Compression: Main stream: H.265/H.264/ Sub stream: H.265/H.264/MJPEG, 30 m IR range, IP67, IK10, 12 VDC, 0.4 A, Max: 5 W 2 x DS-2CD1047G0-L Camera IP bullet ColorVu Lite (imagini color 24/7), 4MP, iluminator white light 30m, lentila fixa 2.8mm, DWDR, 3D DNR, BLC, HLC, ROI, streaming dual, IP67, 12VDC/PoE, 20 fps (2560 x 1440), 1/2.7" Progressive Scan CMOS, Color: 0.001 Lux @ (F1.0, AGC ON), 2.8 mm, horizontal FOV 102°, vertical FOV 56°, diagonal FOV 127°, IR 30 m, Digital WDR, BLC, HLC, 3D DNR, t H.265+ compression, 1 RJ45 10M/100M self-adaptive Ethernet port, 12 VDC, 0.30 A, max. 3.6 W, PoE (802.3af, 36 V to 57 V), 0.20 A to 0.10 A, max. 4.5W, IP67, temperatura de functionare: - 30 °C to 60 °C, dimensiuni: 68.4 x 65.2 x 161.1mm, greutate: 420 g 4 x MEDIA CONVERTOR TP-L
