

Pachet piese si accesorii pentru computere_ISUJ Ialomita

I.D.: 24706896

Data publicarii	14.12.17	Coduri CPV	30237000-9
-----------------	----------	------------	------------

Termenul limita pentru depunere:	17.12.17	Pretul estimativ:	1.033,00 RON
----------------------------------	----------	-------------------	--------------

Descriere: - Placa de baza Pc - 1 buc; - Procesor PC - 1 buc; - Memori RAM DDR4 - 1 buc; - HDD500 GB - 1 buc; - Sursa PC - 1 buc; - Boxe PC 2.0 - 2 buc. - Router - 1 buc Specificatii tehnice: Placa de baza Format - mATX Soclu procesor - 1151 Procesoare suportate- Intel 6th Generation Core i7/i5/i3/Pentium/Celeron Placa video integrata Placa audio integrata Placa retea integrata - 10/100/1000 Mbps Numar SATA III - 4 buc Memorie suportata - DDR4 Memorie maxima - 32 GB Tehnologie- Dual channel Frecventa suportata - 2133 MHz Conectori Beck Panel: - PS/2 Mouse -1 - PS/2 Tastatura - 1 - VGA - 1 - DVI - 1 - RJ-45 LAN -1 - USB 2.0 -4 - USB 3.0 - 2 - Suport audio - 5.1 Procesor PC Recomandat pentru Gaming - DA Socket - 1151 Numar minim nuclee - 2 Frecventa - 3.3 GHz Tehnologie de fabricatie - 14nm Puterea totala disipata - 54W Cooler stock inclus - DA Memorie grafica integrata - minim 1.5 GB Suport memorie - DDR 3, DDR 4 Memorie maxima - 64GB Frecventa memorie - 1333, 1600, 1866, 2133 MHz Suport Dual Channel Memorie 4GB- DDR4 2400 MHz Latenta CAS - maxim 16CL HDD 500 GB SATA-III 7200 RPM Buffer - 64 MB Form factoSursa PC ATX - 500 W Numar ventilatoare - 1 x 120 mm Protectie - SCP, OCP, OVP Conectori minim 20+4 Pin ATX - 1 4 Pin ATX 12V - 1 SATA - 2 Molex - 2 Floppy - 1 Boxe PC 2.0 Puterea RMS (W) gt;= 6 Banda de frecventa - 20-20000 Hz Sateliti - 2 buc. Amplificare - integrata Alimentare USB Buton pornit/oprit Buton reglare volum ROUTER Caracteristici HARDWARE Standarde si Protocoale - IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DDNS Interfata - 1 Port fix Ethernet WAN 1 Port fix Ethernet LAN 3 Porturi Ethernet WAN/LAN configurabile Retea media - 100BASE-TX Cablu UTP cat. 5, 5e Buton reset Sursa interna de alimentare Flash - minim 4 MB DRAM - min 64 MB LED - PWR, SYS, WAN, LAN, WAN/LAN Performanta Sesiune Concomitent - 10000 Functii de baza : - Tip conexiune WAN - Static/Dynamic IP, PPPoE, PPTP, L2TP, Dual Access, Bigpond Cable - DHCP - Server/Client DHCP, Rezervare adresa prin DHCP - Clonare MAC - Modificare adresa MAN WAN/LAN - Setare switch - Port Mirror, Rate Control, Port Configuration, Port VLAN - ACL - Filtrare IP/MAC/URL/WEB - Forwarding - Virtual Server, Port Triggering, DMZ - Echilibrarea traficului - Policy Routing, Link Backup - Rutare - Static routing - Securitate - FTP/SIP/PPTP/IPsec/H.323 ALG, DoS Defence, Ping of Death, IP/MAC Binding - Control trafic - Controlul la?imii de banda, Limitare sesiuni Management Servicii - PPPoE Server, E-Bulletin, Dynamic DNS, UpnP Mentenanta - Setare Timp, Diagnoza, Upgrade Firmware, Factory Defaults/Reboot, Backup/Restore, System Log, Remote Management, Statistici
