

Camera supraveghere IP Dome Hikvision DS-2CD1323G0E-I-28, 2 MP, IR 30 m, 2.8 mm, PoE

I.D.: 106321343

Data publicarii	29.11.24	Coduri CPV	32333200-8
-----------------	----------	------------	------------

Pretul estimativ: 493,34 RON - 493,34 RON

Descriere: Specificatii Senzor: 1/2.8 inch CMOS Progressive Scan Rezolutie video: 1920 x 1080
Sensibilitate: color 0.01 Lux @ (F1.2, AGC pornit), 0.028 Lux @ (F2.0, AGC pornit) Lentila fixa:
2.8 mm Unghi vizual: 114.8° (orizontal), 62° (vertical), 135.5° (diagonala) Distanta iluminator
IR: 30 m Viteza shutter: 1/3 s - 1/100000 s Slow shutter: da Ajustare unghi: Pan 0° - 360°,
Tilt 0° - 75°, Rotation 0° - 360° Functii speciale: filtru IR cut, day&night
(auto/scheduled/day/night), 3D DNR, DWDR, BLC, ROI (1 zona fixa pentru main stream si sub-
stream) Declansare alarma: detectia miscarii, alarma manipulare video, autentificare ilegala
Setari imagine: saturatie, luminozitate, contrast, claritate, AGC si WB ajustabile prin client
software sau browser web Functii generale: anti-flicker, heartbeat, mirror, protectie cu
parola, privacy mask, watermark Compresie video: main stream
H.265+/H.265/H.264+/H.264; sub-stream H.265/H.264/MJPEG Tip H.264: Main Profile/High
Profile/Baseline Profile Tip H.265: Main profile Bit rate video: 32 Kbps - 8 Mbps Main stream:
50Hz: 25fps (1920 x 1080, 1280 x 960, 1280 x 720); 60Hz: 30fps (1920 x 1080, 1280 x
960, 1280 x 720) Sub-stream: 50Hz: 25fps (640 x 480, 640 x 360, 320 x 240); 60Hz: 30fps
(640 x 480, 640 x 360, 320 x 240) Protocol: TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP,
RTSP, RTCP, NTP, IGMP, QoS, UDP API: ONVIF (PROFILE S), ISAPI Live view simultan: pana la 6
canale User/host: pana la 32 de utilizatori (administrator, operator si utilizator) Aplicatie c
