

PIESE DIN SISTEMUL DE SUPRAVEGHERE VIDEO SI MONTAJUL CONFORM ADV1174710/08.10.2020

I.D.: 50619221

Data publicarii 14.10.20 Coduri CPV 35120000-1 31711100-4

Pretul estimativ: 6.344,00 RON - 6.344,00 RON

Descriere: a. Calculatorul de la postul de paza: Desktop PC Tower, Intel Core i5-3470T 2,9 Ghz(frecventa Turbo 3,6 Ghz), 4 GB DDR3, SSD 240 GB, DVD, Licenta Windows 10 Pro 64 bit. Cantitate : 1 bucata; b. Camere IP de interior: Camera IP de interior 2 Megapixeli, turret, IR 30m; 1/2,8" CMOS; Color 0.01 Lux/F1.2; Lentila 2.8mm; Day&Night, D WDR, BLC, 3D DNR; Compresie video: H.265+/H.265/H.264+/H.264; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Detectie miscare; 1 RJ45 10M/100M Ethernet; IP67; Temperatura de operare: - 30°C~+50°C; Alimentare: 12VDC, 0.4A, max. 5W; PoE (802.3af), 0.2-0.1A, max.6.5W; Compatibila cu standardul ONVIF, ISAPI; Cantitate: 8bucati; c. Camera video dome, IP, de exterior: Camera dome IP exterior 2 Megapixeli, dome, IR 30m; 1/2,8" CMOS; Color 0.028 Lux/F2.0; Lentila 2.8mm; Day&Night, WDR 120dB, BLC, 3D DNR; Compresie video: H.265+/H.265/H.264+/H.264; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Detectie miscare; 1 RJ45 10M/100M Ethernet; Cantitate: 4bucati; d. Switch 4 porturi POE: Switch 4-Port 100 Mbps Long-Range PoE. 1 × 10/100 Mbps Hi-PoE , 3 × 10/100 Mbps PoE, 2 × 10/100 Mbps RJ45. IEEE 802.3at/af/bt standard for Hi-PoE port (Max. 60 W port power). IEEE 802.3at/af standard for PoE ports. IEEE 802.3, IEEE 802.3u, and IEEE 802.3x standard. Protectie la supratensiune 6 KV pentru porturile PoE. 250 m in modul extins si 150 m in modul Hi-PoE; Cantitate: 2bucati; e. Camera Analogica de exterior : Camera video Analogica 2 Megapixeli Bullet, High Performance CM