

Automat programabil PLC industrial S7-1200

I.D.: 60821028

Data publicarii	09.09.21	Coduri CPV	38342000-4
-----------------	----------	------------	------------

Pretul estimativ:	11.900,00 RON - 11.900,00 RON
-------------------	-------------------------------

Descriere: Automat programabil PLC industrial S7-1200-6ES7214-1BG40-0XB0 SIMATIC S7-1200, CPU 1214C, compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: AC 85-264 V AC at 47-63 Hz, Program/data memory 100 KB +6ES7231-4HD32-0XB0 SIMATIC S7-1200, Analog input, SM 1231, 4 AI, +/-10 V, +/-5 V, +/-2.5 V, or 0-20 mA/4-20 mA, 12 bit+sign (13 bit ADC) +6ES7232-4HB32-0XB0 SIMATIC S7-1200, Analog output, SM 1232, 2 AO, +/-10 V, 14-bit resolution, or 0-20 mA/4-20 mA, 13-bit resolution +6SL3210-1KE15-8AF2 SINAMICS G120C RATED POWER 5,5 KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178(HXWXD) EXTERNAL 24V +6SL3255-0AA00-4JA2 SINAMICS G Intelligent Operator Panel IOP-2 for SINAMICS G120, G120P G110M, G110D, G120D, G120C ET 200PRO FC-2 Language settings: German, English, French Italian, Spanish Portuguese, Dutch Swedish, Russian Czech, Polish Turkish, Finnish Chinese (simplified) Environmental class during operation: Harmful chemical substances, Class 3C3 according to IEC 60721-3-3: 2002 +6SL3255-0AA00-5AA0 SINAMICS G120 Web Server Module
