

SISTEM VIDEO - INTERFON

I.D.: 70996762

| | | | |
|-----------------|----------|------------|------------|
| Data publicarii | 07.07.22 | Coduri CPV | 42961100-1 |
|-----------------|----------|------------|------------|

| | |
|-------------------|-------------------------------|
| Pretul estimativ: | 37.760,00 RON - 37.760,00 RON |
|-------------------|-------------------------------|

Descriere: POST EXTERIOR IP POE COMPUS : 1X Modul Statie usa videointerfon; Rezolutie camera 2Mpx; FishEye cu infrarosu; WDR; FOV H:180°/V:96°; Submodule max.8; 10M/100M Self-adaptive Ethernet; 4 x IO; IP65; 12 VDC/PoE (IEEE 802.3af); 1-Buton acces; 1XModul cititor Mifare; Intefata conectare: 1IN/1OUT; Alimentare 12VDC 1IN/1OUT; 1XModul apelare videointerfon cu tastatura; Intefata conectare: 1IN/1OUT; Alimentare 12VDC 1IN/1OUT ;1 X Rama montaj aplicat 3 module- 2 BUC, Post interior, 7" Touch-Screen, TFT LCD color 7-inch, display resolution:1024 x 600, 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n, 8-ch alarm input, micro SD card max32GB, 12VDC1A/Standard PoE - 12 BUC, Switch 10 porturi(8xPoE 10/100Mb/s + 2xUPLINK 10/100/1000Mb/s) + 2 x 1000M SFP , 8 porturi PoE IEEE802.3af @15.4W sau IEEE802.3at @30W, Buget PoE max. 123W, Extend On: 250 m @10M/ CAT 5e, 110-240VAC/127W max, W440xH43xD285 - 2 BUC,Yala electromagnetica exterior sursa pentru yala 12v 1.5 a, cutie doza pentru sursa yala ; Kit cablaj necesar plus accesorii ; taguri RFI - 2 BUC. Prestare servicii configurare , cablare, software interfon IP , cablaj necesar pentru toata instalatie, accesorii, mufe RJ45, colier pvc , canal cablu
