

## **AAA8884FDEG/AAB Extindere sistem de supraveghere video cu 10 camere IP si NVR cu 32 de canale video**

I.D.: 45501897

---

|                 |          |            |            |
|-----------------|----------|------------|------------|
| Data publicarii | 08.04.20 | Coduri CPV | 32323500-8 |
|-----------------|----------|------------|------------|

---

Pretul estimativ: 25.450,00 RON - 25.450,00 RON

---

Descriere: NVR 4K, 32 canale 12MP , Inregistrare: 12MP/8MP/5MP/3MP/1080P/720P @25fps/ch., Compresie: H.265+/H.265/H.264;, Redare: 1-16 canale sincronizate;, Latime banda: intrare 256Mbs / iesire 256Mbs, Iesiri video: HDMI 4K (3840 × 2160), VGA 1080P, Interfete externe: 2xUSB, 2 x LAN 10/100/1000Mb, 1 audio, Alarma: 16IN/4 OUT; Capacitate HDD: 4xHDD max 8TB, Tensiune alimentare: 110-220VAC, Consum: <20W; - 1 buc Camera video de exterior iesiri complexe, Rezolutie video: 2 megapixeli (1920 × 1080), Senzor: 1/3 inch Progressive Scan CMOS, Lentila varifocala: 2.8 - 12 mm, Distanta iluminator IR: 30m, Functie speciala: DNR, WDR, BLC, Sensibilitate color: 0.01 Lux la (F1.2,AGC ON), 0 Lux with IR; 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR, Viteza declansator: 1/25 s to 1/100,000 s, Cadre pe secunda: 50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720); 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720), Compresie video: H.264/ MJPEG, Compresie audio: G.711/G.726/MP2L2, Temperatura de functionare: de la -30 pana la +60 grade Celsius, Grad de protectie carcasa: IP66, Setari imagine: Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser, Interfata retea: 1 RJ45 10M/100M Ethernet interface, Protocol: TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP, RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour, Standard: ONVIF, PSIA, CGI, ISAPI, Slot card: Micro SD/SDHC/SDXC card slot incorporat, pana la 64 GB, Alimentare: 12 V DC ± 10%..

---