

Camera supraveghere exterior IP cu iluminare duala Dahua WizSense TiOC Active Deterrence IPC-HFW3849

I.D.: 107309784

Data publicarii 17.12.24 Coduri CPV 32333200-8

Pretul estimativ: 7.815,12 RON - 7.815,12 RON

Descriere: Specificatii Camera Senzor: 1/2.8 inch Progressive scan CMOS Rezolutie video: 8 Megapixeli (3840 x 2160 pixeli) Capabilitate streaming: 3 stream-uri Compresie video: Smart H.265/Smart H.264/AI H.265/AI H.264/H.265/H.264 Cadre/secunda: Main Stream: 3840 x 2160 - 1-30 fps Sub Stream: 704 x 576 - 1-25 fps / 704 x 480 - 1-30 fps Third Stream: 1920 x 1080 - 1-30 fps Video Bit Rate: 3 kbps - 8 mbps Sensibilitate: 0.004 Lux @F1.0 (Color, 30 IRE) 0.0004 Lux @F1.0 (B/W, 30 IRE) 0 Lux cu iluminator Distanta iluminator LED: 40 m Distanta iluminator IR: 50 m Lentila Lentila varifocala: 2.7 - 13.5 mm Diafragma: F1.0 Viteza shutter electronic: Intre 1/3 s - 1/100000 s Unghi de vizualizare: 108°-34°(H) x 56°-19°(V) x 130°-39°(D) Audio Microfon: 2x, incorporat Difuzor: Incorporat Audio IN/OUT: 1/1 Functii Functii speciale: BLC, HLC, WDR, Gain Control, 3D DNR, Detectia miscarii (4 zone), ROI (4 zone), Iluminare Smart, Mirror, 4 Zone private, Defog. Iluminare inteligenta: Ajustare automata a intensitatii iluminarii Eveniment alarma: Detectia miscarii (distinctie intre oameni si vehicule), manipulare video, exceptie, eroare card microSD, conflict IP, tripwire, intruziune, detectie audio, alarma externa, SMD Protectia perimetrului: Incalcarea perimetrului, detectia intrusilor, distinctia intre om/vehicul SMD 4.0: Mai putine alarme false, distanta de detectie crescuta Lumini avertizare: Rosu-albastru Retea Port RJ-45: 1x 10/100 M Interoperabilitate: ONVIF (Profil S/Profil G/Profil T), CGI, P2P, M