

## Router

I.D.: 16044040

---

Data publicarii	11.11.16	Coduri CPV	32413100-2
-----------------	----------	------------	------------

---

Termenul limita pentru depunere:	16.11.16	Pretul estimativ:	3.333,00 RON
----------------------------------	----------	-------------------	--------------

---

Descriere: Compunerea card-uri/module: C891F-K9 Cisco 890 Series Integrated Services Routers PWR-60W-AC-V2 Power Supply 60 Watt AC version 2 for some platforms-1buc SL-890-AIS Cisco 890 Advanced IP Services License 1 CAB-ETH-S-RJ45 Yellow Cable for Ethernet, Straight-through, RJ-45, 6 feet 1 PACK-800 Packaging PIDs for 800 with no 3G and POE 1 CAB-CONAUX Straight serial cable- RJ45 to DB25 male 1 CAB-ACE AC Power Cord (Europe), C13, CEE 7, 1.5M 1 ACS-890-RM-19 Rackmount kit for 890 1 S89UK9-15403M Cisco 890 Series IOS UNIVERSAL 1

Detalii Porturi: 8+2 (8 Switch, 2 WAN) Standarde:802.1d,802.1Q,802.3af,802.1x

Conectori:RJ-45,USB 2.0; Caracteristici Switch:Auto Media Device In/Media Device Cross Over (MDI-MDX), 14 802.1Q VLANs,Filtrare MAC,Four-port 802.3af and Cisco compliant PoE, Switched Port Analyzer (SPAN), Storm Control,Smart ports, Secure MAC address,Internet Group Management Protocol Version 3 (IGMPv3) snooping,802.1x. Caracteristici Securitate: SSL VPN for secure remote access, Hardware-accelerated DES, 3DES, AES 128, AES 192, and AES 256,Public-key-infrastructure (PKI) support,50 IPsec tunnels,Cisco Easy VPN Client and Server, NAT transparency,DMVPN ,Tunnel-less Group Encrypted Transport VPN, VRF-aware IPsec, IPsec over IPv6, Adaptive control technology, Session Initiation Protocol (SIP) application-layer gateway, Cisco IOS Firewall,Dynamic and static port security; Management: Cisco Configuration Professional,Cisco Configuration Express,Cisco Configuration Engine support,Cisco AutoInstall,IP SLA,Cisco IOS Embedded Event Manager (EEM),CiscoWorks,Cisco Security Manager,Telnet, SNMPv3, SSH, CLI, and HTTP management,RADIUS and TACACS+ .

Alte caracteristici: Routing Information Protocol Versions 1 and 2 (RIPv1 and RIPv2),Generic routing encapsulation (GRE) and multipoint GRE (MGRE),Cisco Express Forwarding,Standard 802.1d Spanning Tree Protocol,Layer 2 Tunneling Protocol (L2TP),Layer 2 Tunneling Protocol Version 3 (L2TPv3),Network Address Translation (NAT),Dynamic Host Configuration Protocol (DHCP) server, relay, and client,Dynamic Domain Name System (DNS),DNS Proxy,DNS Spoofing,Access control lists (ACLs),IPv4 and IPv6 Multicast,Open Shortest Path First (OSPF),Border Gateway Protocol (BGP), Performance Routing (PfR),Enhanced Interior Gateway Routing Protocol (EIGRP),Virtual Route Forwarding (VRF) Lite,Next Hop Resolution Protocol (NHRP),Bidirectional Forwarding Detection (BFD),Virtual Router Redundancy Protocol (VRRP) (RFC 2338),HSRP, CDP,Flexible NetFlow (FNF),Integrabil in platforme de management CiscoWorks / Cisco Security Manager; Dimensiuni: (W x D x H cm): 4,45 x 32,28 x 24,84 cm; Interfa?a:8-port 10/100/1000-Mbps managed switch,1-port combo: Gigabit Ethernet (GE - RJ45) sau modul SFP,1-port Fast Ethernet (FE);Memorie:512 MB DRAM,256 MB Flash;Altele:2 ani suport pentru serviciile de înlocuire hardware,va fi livrat cu kitul de montare intr-un rack de comunicatii.

---