

SISTEM DE MONITORIZARE STRES HIDRIC ÎN PLANTAȚII

I.D.: 44288460

Data publicarii 18.10.19 Coduri CPV 39300000-5

Pretul estimativ: 15.645,00 RON - 15.645,00 RON

Descriere: SISTEM DE MONITORIZARE STRES HIDRIC ÎN PLANTAȚII: 3663A Radiation Shield -Spectrum Tehnologies - 3buc x 434,00= 1.302,00 3658A WatchDog 1000 Series Sliding Enclosure - Spectrum Tehnologies - 7buc x 215,00=1.505,00 3667S External Temp Sensor, Micro-Spectrum Tehnologies - 5buc x 388,00=1.940,00 SM150T SM150T SOIL MOISTURE SENSOR Fitted with M12 IP68 connector. NB: CABLE MUST BE ORDERED SEPARATELY 1buc 927,00 SMSC/lw-05 SMSC/lw-05 SMS CABLE 5M, LONG BARE WIRE IP68 M12 connector (f) to bare wire. Connects ML3,SM150T, EQ3, FT1 or PR2 SDI-12 Soil Moisture Sensor to data logger. 200mm flying leads 1buc 118,00 GP1 GP1 GENERAL PURPOSE LOGGER Data Logger/Irrigation Monitor with 2 analogue, 2 resistance, 1 event, 1 counter and 1 alarm channel. Includes DeltaLINK PC software on Disk, RS232 cable (GP1-RS232), alkaline battery and quick-guide (full manual on Disk). 1buc 2.344,00 GP-PBA-X50 GP1 GP-PBA-X50 GP1 PRECISION BRIDGE ADAPTER Provides precision +3V reference for bridge sensor excitation. Accepts signals up to +/- 29mV. Enables GP1 to log tensiometers on CH1 and CH2. Maximum of 2 x GP-PBA-X50 boards per GP1 Logger 1buc 518,00 DEX 70 Electronic Dendrometer 10-70 mm range, 10 ft. Cable - DYNAMAX 1buc 4.691,00 2450L LAQUA twin Ca-11 Calcium Meter A precision meter that can be taken directly to the field • New "Professional Grade" Meter • Measure calcium in nutrient solutions, water samples, and tissue sap • Waterproof pocket-sized meter with digital calibration • Sensors stor