

SISTEM CONTROL ACCES AC-C32

I.D.: 44535432

Data publicarii	15.11.19	Coduri CPV	42961100-1
-----------------	----------	------------	------------

Pretul estimativ:	1.695,00 RON - 1.695,00 RON
-------------------	-----------------------------

Descriere: Sistem control acces AC-C32. Fiecare sistem de control acces va include : Cititor de proximitate Rosslare AC-C32- 1 buc Cititor de proximitate stand-alone cu tastatura, protectie RFI > 20 V/m pana la 1000 MHz, compatibil cu toate cardurile 26-Bit EM, greutate maxima 73 g, conectica intrari : REX - N.O., Intrare auxiliara (In/Monitor), mod monitor - N.C., mod input - N.O., trei nivele de utilizator : Normal, Secure, Master Electromagnet forta NAV-EL-280LED 280 Kg - 1 buc Electromagnet forta minim 280 Kg, alimentare duala 24 V si 12 V, montaj aplicat, contact monitorizare si indicator LED, consum maxim 250mA, suport inclus tip L / Z, EN61000-6-1:2007, EN61000-3-2:2014, EN61000-3-3:2013 Sursa alimentare in comutatie cu acumulator 12V 5-7Ah - 1 buc Sursa in comutatie MEANWELL SCP512 iesire 12 VDC, reglabila +15%/-5%, 0~2.6A, 35.9W, alimentare 85~264VAC, setup timp raspuns 500ms, 30ms/230VAC, functie incarcare acumulator, carcasa metalica de protectie, acumulator 12V 5Ah Buton iesire PB-038B - 1 buc Buton cerere iesire, carcasa metalica, varianta aparenta, EN61000-6-3:2007, EN61000-3-3:2008 Card de proximitate - 10 buc Cartela de proximitate, material ABS, 125 KHz, modulare ASK, ISO/IEC 10536 Cablu special alarmare min. 6 fire - 15 ml Cablu minim 6 fire x 0,22 mm² + ecran, operare -10°C / +80°C, standarde CEI 20-52, CEI 20-35, CEI 20-22 III, IEC 60332-3-24
