

Placa de baza H410M H V2

I.D.: 103384894

Data publicarii	23.09.24	Coduri CPV	30233132-5 30237140-2 30236110-6 30211500-6 30233152-1 31682000-0
-----------------	----------	------------	--

Pretul estimativ: 1.503,00 RON -
1.503,00 RON

Descriere: CPU Support for 10th Generation Intel® Core™ i9 processors/Intel® Core™ i7 processors/Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/Intel® Celeron® processors in the LGA1200 package L3 cache varies with CPU (Please refer "CPU Support List" for more information.) Chipset Intel® H470 Express Chipset Memory Intel® Core™ i9/i7 processors: Support for DDR4 2933/2666/2400/2133 MHz memory modules Intel® Core™ i5/i3/Pentium®/Celeron® processors: Support for DDR4 2666/2400/2133 MHz memory modules 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules (Please refer "Memory Support List" for more information.) Onboard Graphics Integrated Graphics Processor-Intel® HD Graphics support: 1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x HDMI ports, supporting a maximum resolution of 4096x2160@30 Hz * Support for HDMI 1.4 version and HDCP 2.3. Maximum shared memory of 512 MB Audio Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the au
