
Media converter

I.D.: 64069574

Data publicarii	10.12.21	Coduri CPV	32422000-7
-----------------	----------	------------	------------

Pretul estimativ: 350,00 RON - 350,00 RON

Descriere: Specificații Tehnice: Standarde de operare: IEEE802.3z/AB, 10/100/1000Base-T and 1000Base-SX/LX/HX RJ-45 Port: Auto-MDI/MDIX Network Cable: Twisted pair Cat.5 UTP Cable: 100m Fiber Cable: SMF: 8.3/125,8.7/125,9/125,10/125 (20~120Km) Cerinte de consum: DC5V2A (Sursa externa: AC100V-AC240V/50-60HZ) LED: Power, FX SD, FX Link/Act, TX 100, TX FDX, TX Link/Act. Lumini indicatoare: PWR, FX Link/act, FX 1000M, TX 1000M, TX 10/100M, TX Link/act. Timp de raspuns (delay): <0.9s Temperatura de pastrare: -30~ 60 °C Temperatura de operare: 0 ~ 50 °C Temperatura de functionare: 0 ~ 70 °C Conditii de umiditate : 5%~90% (fara condens) Dimensiuni - valabile pentru modelul cu 1 slot SFP (WxDxH): 40x110x140mm (sursa interna) / 26x70x93mm (sursa interna).
