

Micro Converter SDI to HDMI wPSU, Blackmagic Design +CABLU USB LA SERIAL RS232 0.3M

I.D.: 86448025

Data
publicarii 28.08.23

Coduri CPV

32351000-8

Pretul
estimativ: 1.005,99 RON - 1.005,99 RON

Descriere: Intrari Video 1 x 3G/HD/SD-SDI ,1 x HDMI tip A Iesiri Video 1 x 3G/HD/SD-SDI ,1 x HDMI tip A Alte
Intrari/Iesiri 1 x Micro-USB Standarde video acceptate SDI:1080p: 60 / 59,94 / 50/30 / 29,97 /
25/24 / 23,98 1080i: 60 / 59,94 / 50 ,720p: 60 / 59.94 / 50 NTSC SD: 525i 59,94 PAL SD: 625i
50 HDMI:1080p: 60 / 59,94 / 50/30 / 29,97 / 25/24 / 23,98,1080i: 60 / 59,94 / 50,720p: 60 /
59.94 / 50 NTSC SD: 525i 59,94 PAL SD: 625i 50 Compatibilitate SDI SMPTE 425M / 424M /
372M / 296M / 292M / 259M Spatiu de culoare SDI SDI: YUV; HDMI: YUV Sisteme de operare
suportate,MacOS 10.12 Sierra,MacOS High Sierra 10.13 sau mai recent,Windows
8.1,Windows 10 Consum de energie 2,5 W Interval operational de tensiune De la 4,4 pana la
5,25 VDC Temperatura de operare de la 0 pana la 40° C Temperatura de depozitare De la -
20 la 60° C Umiditate relativa De la 0 pana la 90% Tip conexiune:Serial RS-232 Conector
1:USB tip A tata Conector 2:1 x Sub-D 9 pini Serial RS-232 tata Chipset:Prolific Rata transfer
date pana la:230.4 Kb/s Lungime:35cm Cerinte de sistem:WIN98, WIN ME, WIN 2K, WIN 2003,
WIN XP, WIN Vista, WIN 7, WIN 8, WIN 10, LINUX and Mac OS 8.6/9/10