

ACHIZITIE DIRECTA DE SERVER

I.D.: 16520960

| | | | |
|-----------------|----------|------------|------------|
| Data publicarii | 06.12.16 | Coduri CPV | 48820000-2 |
|-----------------|----------|------------|------------|

| | | | |
|----------------------------------|----------|-------------------|---------------|
| Termenul limita pentru depunere: | 09.12.16 | Pretul estimativ: | 80.000,00 RON |
|----------------------------------|----------|-------------------|---------------|

Descriere: Denumire produs: server Cantitate necesara de achiziționat: 2 bucati Server Supermicro SuperServer 6028R-E1CR12H, 2x Procesor Intel® Xeon® E5-2630 v4 2.2GHz Broadwell, 8x 16GB RDIMM DDR4, 2x 2TB SATA 7.2K + 5x 400GB SSD + 2x 240GB SSD, LFF 3.5 inch, Windows Server 2012 R2 sau echivalent Caracteristici tehnice: Denumire:Server Supermicro SuperServer 6028R-E1CR12H, 2x Procesor Intel® Xeon® E5-2630 v4 2.2GHz Broadwell, 8x 16GB RDIMM DDR4, 2x 2TB SATA 7.2K + 5x 400GB SSD + 2x 240GB SSD, LFF 3.5 inch, Windows Server 2012 R2 Garantie comerciala:12 luni Garantie de conformitate:24 luni Model Platforma SuperServer Recomandat pentru Enterprise Business Procesoare incluse 2 Procesor Intel® Xeon® Processor E5-2630 v4 (25M Cache, 2.20 GHz) Memorie RAM Memorie RAM inclusa Da Capacitate RAM 128 GB Tip memorie ECC Tip RAM DDR4 DIMM RDIMM Frecventa 2400 MHz Standard PC4-19200 Modulele 1-8: 16384 MB/modul Memorie RAM Maxima Numar sloturi RAM 16 Compatibilitate DIMM RDIMM, LRDIMM Memorie maxima 1024 GB Observatii 8 DIMM-uri per procesor Capacitate max 512GB RDIMM Capacitate max 1TB LRDIMM Capacitate max 2TB ECC 3DS LRDIMM Stocare Hard disk inclus Da Capacitate 2x 2000 GB 5x 400 GB 2x 240 GB Interfata SATA SSD Viteza de rotatie 7200 rpm Tip 3.5 inch Hot Plug Da Detalii 2x Intel S3510 240GB SSD DataCenter , SATA 6Gb/s, MLC 2.5 7.0mm, 16nm 0.3DWPDP , SATA 6Gb/s, MLC 2.5 7.0mm, 16nm 4x Intel S3610 400GB SSD DataCenter HET , SATA 6Gb/s, MLC 2.5 7.0mm 20nm 3DWPDP 1x Intel S3710 400GB SSD DataCenter HET , SATA 6Gb/s, MLC 2.5 7.0mm, 20nm 10DWPDP 2x Seagate 3.5 2TB SATA 6Gb/s 7.2K RPM 128M Enterprise ST2000NM0033 Compatibilitate Stocare Compatibilitate HDD 3.5 inch Compatibilitate Hot Plug Da Placa De Baza Procesoare suportate 2 Socket 2011-3 Chipset Intel C612 Video integrat ASPEED AST2400 BMC Sloturi PCI Express 3.0 x16 x1 Sloturi PCI Express 3.0 x8 x6 Observatii 1x PCI-E 3.0 x16 slot 6x PCI-E 3.0 x8 slots Slot 1 2 occupied by controller and JBOD Expansion Port Controller Controller retea Intel X540 Dual Port 10GbE Detalii controller retea 2x RJ-45, 10/100/1000/10000 Controller stocare LSI 3108 Suport RAID 0, 1, 5, 6, 10, 50, 60 Detalii controller stocare 2GB cache Conectori Back Panel Serial x1 Video x1 USB 2.0 x2 USB 3.0 x2 RJ-45 x3 (1 dedicat management LAN) Carcasa Tip Rack 2U Sloturi expansiune x7 Greutate 17.4 kg Dimensiuni 648 x 437 x 89 mm Nr surse suportate 2 Capacitate Pana la 12x LFF (3.5 inch) Alte Detalii Alte detalii IPMI controller advanced management features e.g., BIOS Firmware upgrade and provisioning Sursa Surse incluse 2 Redundanta Da Tip Hot Plug Putere 920 W Certificare Platinum Sistem De Operare Sistem de operare Windows Server 2012 Editie R2 Standard
