

Contactor AC LT1 225A/400V

22.02.22 Coduri CPV 31681000-3 Data publicarii Pretul 2.505,00 RON - 2.505,00 RON estimativ: Descriere: Technical characteristics: - Operation class: AC3 - Rated operating voltage of power contactors: up to 1000V;50/60Hz - Rated current: 115-800A - Surge voltage wear resistance: >8000V - Rated operating voltage of the coil: 12/24/36/48/110/230/400 - Electrical wear resistance (number of cycles): ≥10000000 - Mechanical wear resistance (number of cycles): ≥10000000 - Number of cycles (switching on) per hour: 200 - Power dissipation per pole: from 16 to 80W - Ambient temperature: $-10^{\circ} \div 65^{\circ}$ C - Maximum altitude: up to 2000M Advantages: - High reliability of the current parameters - Secure separation of the power contacts - Resistant to UV rays - Easy mounting - Long life Functions: - Frequently switching ON/OFF of electrical circuits under load - Developing of systems for control of consumers -Operational element in control boards - Protection of loads and electrical devices in production and exploitation - Control of motors in normal or heavy operating environments Applications: - Industry - Building construction - Administrative and public buildings Mounting: On a DIN rail or using screws to a flat surface in a vertical position with maximum incline of ±5° Standards: EN60947-1; EN60947-4-1; EMC

I.D.: 66608761