

MIXER DYNACORD CMS 1000-3 CU RACK CASE SI ACCESORII

I.D.: 51574199

| | | | |
|-----------------|----------|------------|------------|
| Data publicarii | 13.11.20 | Coduri CPV | 32342410-9 |
|-----------------|----------|------------|------------|

Pretul estimativ: 5.361,34 RON - 5.361,34 RON

Descriere: Mixer pasiv/analogic Dynacord CMS 1000-3 canale (Mono + Stero): 6 (mic / linie) + 4 (mic / stereo) auxiliare (MON, FX, AUX): 2 Pre, 2 Post, 2 Pre/Post comutabil gain microfon (mono/ stereo): 0 la +60dB / +10 la +60dB gain linie/CD/USB (stereo): -10 la +20dB distorsiuni armonice THD la 1 kHz, MBW = 80 kHz: mai mic de 0.005% raspuns in frecvente -3 dB, ref. 1 kHz: 15 Hz - 70 kHz crosstalk intercanale la 1 kHz: mai mic de -80dB Fader si FX/AUX/MON-Send attenuation > 85 dB Channel to Channel < -80 dB sensibilitate de intrare (cu controalele de nivel la maxim) MIC / LINE (Mono) / LINE (Stereo) / CD (Stereo): -74 dBu (155 μ V) / -54 dBu (1.55 mV) / -34 dBu (15.5 mV) / -34 dBu (15.5 mV) nivel maxim: intrari de microfon +21dBu intrari mono linie / stereo +41 dBu / +30dBu; alte intrari si iesiri: +22dBu zgomot de intrare echivalent, intrare microfon 150 Ohmi: -130dBu EQ pe canale: joase ± 15 dB/60Hz medii mono ± 15 dB/100Hz-8kHz medii stereo ± 12 dB/2.4kHz inalte ± 15 dB/12kHz EQ master pe 11 benzi ± 10 dB: 63, 125, 250, 400, 630, 1k, 1.6k, 2.5k, 4k, 6.3k, 12k Hz filtru de taiere a joaselor la 80Hz, 18dB/octava filtru pentru voce comutabil filtru feedback, MON 1/2: 70Hz - 7kHz, Notch, -9dB procesor de efecte dual pe 24/48 biti efecte: 100 de fabrica + 20 utilizator, Tap-Delay afisaj: 128 x 64 px OLED interfata audio digitala integrata cu conexiune USB: 4 intrari/ 4 iesiri, convertor AD/DA 24 biti, rate de esantionare 44.1/48/88.2/96kHz interfata MIDI integrata phantom power comutabil pe grupe +4
