

NVR Hikvision AcuSense DS-7608NXI-I2/SC, 8 canale, 12 MP, 80 Mbps, POS, functii smart

I.D.: 82314896

Data publicarii	16.05.23	Coduri CPV	32323500-8
-----------------	----------	------------	------------

Pretul estimativ: 952,21 RON - 952,21 RON

Descriere: Specificatii Retea Protocol retea: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS Latime banda intrare: 80 Mbps Latime banda iesire: 256 Mbps Interfata: 2 × Port RJ-45 (10/100/1000 Mbps), auto-adaptiv Intrare/iesire alarma: 4/1 Software management: Hik-Connect & DDNS (Dynamic Domain Name System) pentru management de retea usor Inregistrare Rezolutie inregistrare: 32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF Compresie video: H.265+/H.265/H.264+/H.264/MPEG4 Inregistrare Dual Stream: da Compresie audio: G.711ulaw/G.711alaw/G.722/G.726/MP2L2 Audio/Video Iesiri Audio: 1-ch RCA (Linear, 1 KΩ) Intrari video IP: 8 × canale, rezolutie pana la 12 MP / canal *32 MP si 24 MP sunt disponibile pentru 1 canal cand modul de rezolutie HD este activat Iesiri video: 1 × HDMI, 1 × VGA Capacitate decodare: 16-ch @ 1080p Rezolutie redare: HDMI: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz Mod iesire video: HDMI/VGA Iesire CVBS: 1-ch, BNC (1.0 Vp-p, 75 Ω), rezolutie: PAL: 704 × 576, NTSC: 704 × 480 Intrare audio two-way: 1-ch, RCA Protectie perimetrala* Reducere alarma falsa: pana la 4 canale de 2 MP (H.264 / H.265), pana la 12 reguli in total Recunoastere faciala* Detectare si analiza faciala: comparare imagini f
