



## Refectoare tip WASH minim 37 LED (quad color RGBW) buc. 10

I.D.: 70787614

Data publicarii 04.07.22 Coduri CPV 31518100-1

Termenul limita pentru depunere: 07.07.22

Descriere: SPECIFICATIONS OPTICAL Light Source: 37 LEDs (quad-color RGBW) 25 W, (1.5 A), 50,000 hours life expectancyColor Temperature (range): 2,800 to 10,000 KBeam Angle: 9.3° to 33.9°Field Angle: 11.6° to 49.5°Zoom Angle: 11.6° to 49.5°Lumens - Source: 17,000Lumens - Output: 13,440Illuminance (11.6°): 18,260 lux @ 5 mIlluminance (49.5°): 1,556 lux @ 5 mSelectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz DYNAMIC EFFECTS Pan and Tilt: 540°/230°Pan and Tilt Ranges: 180°, 360°, 540° Pan/90°, 180°, 230° TiltDimmer: ElectronicShutter/Strobe: ElectronicZoom: MotorizedStrobe Rate: 0 to 20 HzStandalone Color Mixing: YesColor Temperature Presets: YesDim Curves: 4Built-in Automated Programs: YesCustomizable Programs: NoRecall Custom Programs: No CONSTRUCTION / PHYSICAL Dimensions: 15.51 x 11.73 x 18.50 in (394 x 298 x 470 mm)Weight: 38.5 lb (17.46 kg)Exterior Color: BlackHousing Material: High-impact flame-retardant polymer CONNECTIONS Power Connection: Edison (local) plug to Neutrik® powerCON®Power Input: Neutrik® powerCON®Power Output: Neutrik® powerCON®Data Connectors: 3- and 5-pin XLR Cable Length (power): 5 ft (1.5 m) CONTROL Control Protocol: DMX, RDM DMX Channels: 21, 62, 71, 107Modes/Personalities: 4 personalities ELECTRICAL Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)Power Linking: 2 units @ 120 V; 4 units @ 208 V; 4 units @ 230 VPower and Current: 661 W, 5.60 A @ 120 V, 60 HzPower and Current: 653 W, 3.136 A @ 208 V, 60 HzPower and Current: 650 W, 2.85 A @ 230 V, 50 Hz CERTIFICATIONS / QUALIFICATIONS CE, MET, FCCIP Rating: IP20, dry location WHAT'S INCLUDED Rogue R3X WashNeutrik® powerCON® power cord2 Omega brackets with mounting hardware OPTIONAL ACCESSORIES Professional Clamps: CTC-50HC, CTC-50HCNSafety Cable: SC-07Neutrik® powerCON® cablesDMX CablesFlight Case: CP4CASER3WUPL0AD 08