

Camera supraveghere exterior IP Hikvision DS-2CD1053G0-I-28, 5 MP, IR 30 m, 2.8 mm, PoE

I.D.: 62655363

Data publicarii	03.11.21	Coduri CPV	35125300-2
-----------------	----------	------------	------------

Pretul estimativ: 925,23 RON - 925,23 RON

Descriere: Specificatii Senzor: 1/2.7 inch CMOS Progressive Scan Rezolutie video: 2560 x 1920
Sensibilitate: color 0.01 Lux @ (F1.2, AGC pornit), 0.028 Lux @(F2.0, AGC pornit) Lentila fixa:
2.8 mm Unghi vizual: 100° (orizontal), 74° (vertical), 130° (diagonala) Distanța iluminator IR:
30 m (850 nm) Viteza shutter: 1/3 s - 1/100000 s Slow shutter: da Ajustare unghi: Pan 0° -
360°, Tilt 0° - 180°, Rotate 0° - 360° Functii speciale: filtru IR cut, day&night
(auto/scheduled/day/night), 3D DNR, WDR (120 dB), BLC, ROI (1 zona fixa pentru main stream
si sub-stream) Declansare alarma: detectia miscarii, manipulare video, deconectare retea,
conflict adresa IP, autentificare ilegala, eroare HDD, HDD plin Setari imagine: saturatie,
luminozitate, contrast si claritate ajustabile prin client software sau browser web Functii
generale: heartbeat, mirror, protectie cu parola, privacy mask, watermark, filtru adresa IP
Compresie video: main stream H.265/H.264; sub-stream H.265/H.264/MJPEG Tip H.264: Main
Profile/High Profile H.264+: suporta Main stream Tip H.265: Main Profile H.265+: suporta
Main stream Bit rate video: 32 Kbps - 8 Mbps Main stream: 50Hz: 12.5fps (2560x1920), 20fps
(2560x1440), 25fps (2304x1296, 1920x1080, 1280x720); 60Hz: 15fps (2560x1920), 20fps
(2560x1440), 30fps (2304x1296, 1920x1080, 1280x720) Sub-stream: 50Hz: 25fps (640x480,
640x360, 320x240); 60Hz: 30fps (640x480, 640x360, 320x240) Stocare: NAS (NFS,
SMB/CIFS) Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, R
