
Buton de incendiu adresabil Teletek SENSOIRIS MCP150, aparent, izolator scurtcircuit, ABS

I.D.: 76219201

Data publicarii	06.12.22	Coduri CPV	31625000-3
-----------------	----------	------------	------------

Pretul estimativ: 511,75 RON - 511,75 RON

Descriere: Buton de incendiu adresabil Teletek SENSOIRIS MCP150, aparent, izolator scurtcircuit, ABS
Specificatii Tip buton: adresabil Element: resetabil (flexibil) Modul izolator la scurtcircuit
Protocol: TTE Compatibil: centrale IRIS LIGHT, SIMPO Cablu: 0.4 - 2.0 mm² Indicator LED
Montaj: aparent Material: ABS, rosu Grad protectie: IP40 Certificat: EN54-11, EN54-17
Tensiune: 15 - 32 VDC (alimentat de la centrala) Consum fara comunicare: max 125 µA @ 27 VDC
Consum comunicare: 160 µA @ 27 VDC Consum in mod incendiu: 3 mA Temperatura de functionare: -10°C - 60°C Umiditate: 93% ±3% @ 40°C Dimensiune: 90 x 90 x 57 mm
Greutate: 175 g Pachetul contine Buton de incendiu adresabil Teletek SENSOIRIS MCP150
Unealta de test si reset
