

## Proiecte si sisteme supraveghere video si echipament de instalare in municipiul Calafat si satele apartinatoare

I.D.: 10297173

---

Data publicarii	24.11.15	Coduri CPV	35125000-6
-----------------	----------	------------	------------

---

Termenul limita pentru depunere:	03.12.15	Pretul estimativ:	104.839,00 RON
----------------------------------	----------	-------------------	----------------

---

Descriere: 5 buc Speed Dome IP Exterior cu IR - True Day/Night, 3D DNR, 120db True WDR; 3D intelligent positioning; 1/1.9 Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.002 Lux/F:1.5; BW: 0.0002 Lux/F:1.5; ICR; Zoom optic: 23x; Zoom digital: 16x; Lentila: 5.9~135.7mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR:200m, ajustabila de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP66; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -30°C~+60°C; Standard: IP66, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI 9 buc 3 Megapixel, Bullet Camera cu IR 80m (4xEXIR); 1/3 Progressive scan CMOS; 0.07 Lux/F1.2; Lentila fixa: 6mm; DayNight;, D-WDR, BLC, 3D DNR; ROI; Compresie: H264; Rezolutie max.: 2048x1536 / 20fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; NAS; Detectie miscare; ONVIF, PSIA, CGI; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP66 Licenta 14 canale video Milestone Express 2014 6 buc Cofret metalic IP65 400x300x210 6 buc Antene wireless AirGrid M5-HP-23 4 buc HDD 4TB 7200rpm WD Purple 16 buc Media Convertor Gigabit -SFP slot 1000/100/10Tx 2 buc calculator i5 /4Gb RAM/500 Gb HDD/DVDRW + tastatura/mouse 2 buc Monitor 27" AOC sau Samsung 8 buc Switch Allied Telesis 5 porturi 10/100 Mb int. PSU 1 buc SSD 120 Gb 2 buc 16 Gb DDR3 1600 Mhz 1 buc Tastatura/Joystick 2.899,00 lei 2.899,00 lei Controller IP; 3 axe; Controleaza pana la 256 echipamente IP; 7" TFT touch screen la 800x480; Audio 1IN/1OUT; 1 RS-485; 1 RS-232; 1 USB2.0; Alimentare: DC 12V/15W;

---