



COMPONENTA SISTEM VIDEO IP + SWITCH + ROLA CABLU

I.D.: 90517437

Data publicarii 07.12.23 Coduri CPV 32581100-0 32422000-7 32333200-8

Pretul estimativ: 5.915,00 RON - 5.915,00 RON

Descriere: 4MP, turret, microfon, IR 30m; 1/3" CMOS; Color: 0.028 Lux/F2.0; Lentila 2.8mm; Day&Night, D WDR, BLC, HLC, 3D DNR; Compresie video: H.265+/H.265/H.264+/H.264; Rezolutie max.:1920 x 1080@25fps; Third stream; Detectie miscare; Built-in microSD slot, max. 256 GB, 1 RJ45 10M/100M Ethernet; IP67; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC, 0.34A, max. 4W; PoE (802.3af), 0.2-0.1A, max. 5W; Compatibila cu standardul ONVIF, ISAPI, SDK SWITCH 16 PORTURI POE +2 porturi gigabit Conductor de Cupru (Cu) plin, cu diametrul : 0.475 mm - Izolatie cuprului : PE - Numar perechi : 4 perechi torsadate - Manta : PVC de culoare gri - Ambalaj standard : cutii de 305 m. - Diametru exterior cablu : 6.3 mm - Frecventa maxima de operare : 250 MHz - Impedanta : 100 ohm +- 20% ohm 101-250 MHz - Rezistenta conductorului : max. 73.2 ohm/km - Capacitatea mutuala : max. 48 nf/km - Tensiune nominala de lucru : max. 230 V - Tensiune de incercare : max. 700 V - Rezistenta izolatiei : 5.000 Mohm km (500 VDC) - Raza de curbura : aprox. 8 x O cablului
