

## **Camera de supraveghere Speed Dome IP Hikvision DS-2DE4425IW-DE +DS1602ZJ,NETWORK VIDEO RECORDER CU 1**

I.D.: 42698716

Data publicarii 10.05.19 Coduri CPV 35125300-2 32323500-8

Pretul estimativ: 15.404,40 RON - 15.404,40 RON

Descriere: Rezolutie video: 2560 x 1440 pixeli Lentila: 4.8 - 120 mm Cadre/secunda: 25 FPS Zoom optic: 25X Zoom digital: 16X Unghi vizualizare: 59.5° - 2.6° Sensibilitate: 0.005 LUX Numar presetari: 300 Numar scenarii patrulare: 8 (32 presatari pentru fiecare scenariu) Numar zone Privacy Mask: 24 Viteza PAN: 0.1°/s - 80°/s Viteza TILT: 0.1°/s - 80°/s Capacitate de stocare: card microSD de pana la 256 GB (cardul nu este inclus) Port: 1x RJ45 10 Mbps/100 Mbps Temperatura de functionare: -30°C pana la +65°C Alimentare: 12 Vcc, PoE+ Consum maxim: 18 W Dimensiuni: 165.4 x 290 mm Greutate: 2 Kg Protocol retea: TCP/IP, DHCP, HIK Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS Latime banda intrare: 160 Mbps Latime banda iesire: 160 Mbps Interfata: 1x Port RJ-45 (1000M) Compatibilitate Smart Phone: iPhone, iPad, Android POE (Power Over Ethernet - Alimentare prin cablul de retea) Interfata: 16x RJ-45 10/100 Mbps Alimentare maxima: 120W Standarde suportate: 802.3af si 802.3at Inregistrare Rezolutie inregistrare: 8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2 CIF/CIF/QCIF Compresie video: H.264+/H.264 Audio/Video Comunicare bidirectionala: 1x canal RCA (Utilizand primul canal de intrare audio) Intrari/iesiri Audio: 1/1 RCA Iesiri video: 1x HDMI, 1x VGA Rezolutie redare: HDMI: 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz VGA: 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz