

SWITCH GIGABIT 8 PORTURI

I.D.: 47520606

Data publicarii	22.06.20	Coduri CPV	32420000-3
-----------------	----------	------------	------------

Pretul estimativ: 170,00 RON - 170,00 RON

Descriere: CARACTERISTICI GENERALE caracteristici: Standards and Protocols IEEE802.3, 802.3u, 802.3ab, 802.3x CSMA/CD, TCP/IP Basic Function Wire-speed Performance MAC Address Auto-Learning and Auto-aging IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode Backbound Bandwidth 16Gbps MAC Address Table 4k Forwarding Rate 10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port 1000BASE-T: 1488000pps/port Transmission Method Store-and-Forward Ports 8 10/100/1000Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX) Network Media 10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ù STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ù STP (maximum 100m) 1000Base-T: UTP category 5, 5e cable (maximum 100m) LED Indicators Power, 10/100M, 1000M Safety & Emission FCC, CE Dimensions (W*D*H) 7.9*5.5*1.1 in. (200*140*28 mm) Environment Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing Power External Power Adapter cf ref auto 490
